



Safety data sheet

Page: 1/16 Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 11.12.2023 Version: 6.0 Date / Previous version: 17.11.2023 Previous version: 5.0 Product: ARDROX 3140, Aerosol

(ID no. 30706300/SDS_GEN_GB/EN) Date of print 12.12.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ARDROX 3140, Aerosol

UFI: R9JC-DF5R-T000-2SDA

1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended use: corrosion inhibitor

Not recommended use: Uses other than recommended

1.3. Details of the supplier of the safety data sheet

<u>Company:</u> Chemetall Ltd. Napier House, Auckland Park Bletchley, MK1 1BU Great Britain +44 1908 649333 sds.global-chemetall@basf.com

1.4. Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

Page: 2/16 Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 11.12.2023 Version: 6.0 Date / Previous version: 17.11.2023 Previous version: 5.0 Product: ARDROX 3140, Aerosol

(ID no. 30706300/SDS_GEN_GB/EN) Date of print 12.12.2023

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.
STOT SE 3	H336 May cause drowsiness or dizziness.
Flam. Aerosol 1	H222 Extremely flammable aerosol.
Flam. Aerosol 1	H229 Pressurized container: May burst if heated.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Pictogram:



Signal Word: Danger

Hazard Statement:	
H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
Precautionary Staten	nents (Prevention):
P251	Do not pierce or burn, even after use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.
P242	Use non-sparking tools.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P211	Do not spray on an open flame or other ignition source.
P273	Avoid release to the environment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

Precautionary Statements (Response):

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 11.12.2023 Version: 6.0 Date / Previous version: 17.11.2023 Previous version: 5.0 Product: ARDROX 3140, Aerosol

(ID no. 30706300/SDS_GEN_GB/EN) Date of print 12.12.2023

Page: 3/16

P312 P370 + P378 P301 + P310 P303 + P361 + P353	Call a POISON CENTER or physician if you feel unwell. In case of fire: Use water spray for extinction. IF SWALLOWED: Immediately call a POISON CENTER or physician. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P331	Do NOT induce vomiting.
Precautionary Statemen	ts (Storage):
P410 + P412	Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F.
P403 + P233 P403 + P235 P405	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Precautionary Statemen P501	ts (Disposal): Dispose of contents and container to hazardous or special waste collection point.

Labeling of special preparations (GHS): EUH066: Repeated exposure may cause skin dryness or cracking.

Hazard determining component(s) for labelling: Hydrocarbons, C6, isoalkanes, <5% n-hexane, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

2.3. Other hazards

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Container is under pressure. Protect from sun and temperatures above 50 °C. Do not open with force or incinerate even after use. Do not spray into flames or onto glowing objects.

The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

organic compounds

Page: 4/16 Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 11.12.2023 Version: 6.0 Date / Previous version: 17.11.2023 Previous version: 5.0 Product: ARDROX 3140, Aerosol

(ID no. 30706300/SDS_GEN_GB/EN) Date of print 12.12.2023

Hazardous ingredients (GHS) Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics Content (W/W): >= 25 % - < 30 % Asp. Tox. 1 CAS Number: 64742-48-9 Flam. Liq. 3 STOT SE (Central nervous system) 3 EC-Number: 919-857-5 **REACH registration number: 01-**(drowsiness and dizziness) H226, H304, H336 2119463258-33 EUH066 Hydrocarbons, C6, isoalkanes, <5% n-hexane Content (W/W): >= 3 % - < 5 % Asp. Tox. 1 CAS Number: 64742-49-0 Flam. Liq. 2 **REACH** registration number: 01-Skin Corr./Irrit. 2 2119484651-34 STOT SE 3 (drowsiness and dizziness) Aquatic Chronic 2 H315, H411, H225, H304, H336 Sulfonic acids, petroleum, sodium salts Content (W/W): >= 1 % - < 2 % Skin Corr./Irrit. 2 CAS Number: 68608-26-4 Eye Dam./Irrit. 2 EC-Number: 271-781-5 H319, H315 Hexane Content (W/W): >= 0.1 % - < 0.2 % Flam. Liq. 2 CAS Number: 110-54-3 Repr. 2 (fertility) EC-Number: 203-777-6 Asp. Tox. 1 INDEX-Number: 601-037-00-0 STOT RE 2 Skin Corr./Irrit. 2 STOT SE 3 (drowsiness and dizziness) Aquatic Chronic 2 H225, H304, H315, H336, H361f, H373, H411 Differing classification according to current knowledge and the criteria given in Annex I of Regulation (EC) No. 1272/2008 Asp. Tox. 1 Flam. Liq. 2 Skin Corr./Irrit. 2 Repr. 2 (fertility) STOT SE 3 (drowsiness and dizziness) STOT RE 1 Aquatic Chronic 2

Page: 5/16 Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 11.12.2023 Version: 6.0 Date / Previous version: 17.11.2023 Previous version: 5.0 Product: ARDROX 3140, Aerosol

(ID no. 30706300/SDS_GEN_GB/EN) Date of print 12.12.2023

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Keep warm, calm and covered up. Never give anything by mouth to an unconscious person. In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

If inhaled:

Immediate medical attention required. Remove the affected individual into fresh air and keep the person calm. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:

If symptoms persist, seek medical advice. Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution.

On ingestion:

Summon medical aid without delay. Do not induce vomiting due to aspiration hazard. Rinse mouth immediately with water. Keep at rest.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: aspiration pneumonia, dazed state, skin irritation, dizziness, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: If swallowed, in the event of vomiting, risk of product entering the lungs. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Symptomatic treatment (decontamination, vital functions). Antidote: No known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media: carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons: water jet

5.2. Special hazards arising from the substance or mixture

Page: 6/16

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 11.12.2023 Version: 6.0 Date / Previous version: 17.11.2023 Previous version: 5.0 Product: ARDROX 3140, Aerosol

(ID no. 30706300/SDS_GEN_GB/EN) Date of print 12.12.2023

Endangering substances: carbon oxides, sulfur oxides Advice: Cool containers exposed to fire with water. Decomposition, pressure build-up and bursting of containers may occur.

5.3. Advice for fire-fighters

Special protective equipment: Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not discharge into the subsoil/soil. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Handle with care - avoid bumps, friction and impact. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Page: 7/16 Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 11.12.2023 Version: 6.0 Date / Previous version: 17.11.2023 Previous version: 5.0 Product: ARDROX 3140, Aerosol

(ID no. 30706300/SDS_GEN_GB/EN) Date of print 12.12.2023

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: Paper/Fibreboard, tinned carbon steel (Tinplate) Further information on storage conditions: Keep container dry. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions.

Storage stability: Storage temperature: < 50 °C Storage duration: 36 Months

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

74-98-6: propane

	(WEL/EH 40 (UK)) Included in the regulation, but with no data values - See the regulation for further details
106-97-8: butane	
	TWA value 1,450 mg/m3 ; 600 ppm (WEL/EH 40 (UK))
	STEL value 1,810 mg/m3 ; 750 ppm (WEL/EH 40 (UK))
	Ceiling limit value/factor: 15 min
110-54-3: Hexane	
	TWA value 72 mg/m3 ; 20 ppm (WEL/EH 40 (UK))
	TWA value 72 mg/m3 ; 20 ppm (OEL (EU))
	indicative
110-54-3: Hexane	Ceiling limit value/factor: 15 min TWA value 72 mg/m3 ; 20 ppm (WEL/EH 40 (UK)) TWA value 72 mg/m3 ; 20 ppm (OEL (EU))

Biological limit values (BLV)

No data available.

Components with DNEL

64742-48-9: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Page: 8/16

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 11.12.2023 Version: 6.0 Date / Previous version: 17.11.2023 Previous version: 5.0 Product: ARDROX 3140, Aerosol

(ID no. 30706300/SDS_GEN_GB/EN) Date of print 12.12.2023

worker: Long-term exposure- systemic effects, dermal: 208 mg/kg bw/day worker: Long-term exposure- systemic effects, Inhalation: 871 mg/m3

110-54-3: Hexane

worker: Long-term exposure- systemic effects, Inhalation: 75 mg/m3

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Personal protective equipment

Respiratory protection:

Respiratory protection required if exposure limit (if available) may be exceeded (Combination filter EN 14387 AX-P)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1) nitrile rubber (NBR) - 0.4 mm coating thickness butyl rubber (butyl) - 0.7 mm coating thickness Performance level 6, corresponding to a breakthrough time of >480 min according to EN ISO 374-1 The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Eye protection: Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection: Chemical resistant protective clothing according to DIN EN 13034 (Type 6)

General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

Environmental exposure controls

For information regarding environmental exposure controls, see Section 6.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form:

aerosol

Page: 9/16

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 11.12.2023 Version: 6.0 Date / Previous version: 17.11.2023 Previous version: 5.0 Product: ARDROX 3140, Aerosol

(ID no. 30706300/SDS_GEN_GB/EN) Date of print 12.12.2023

	under pressure	
Colour:	dark brown	
Odour:	of hydrocarbons	
pH value:		
	substance/mixture is a gas	
Melting point:		
	Study technically not feasible.	
onset of boiling:		
	not determined	
Flash point:	45 °C	(ISO 3679)
	without propellant	
Flammability:	Extremely flammable aerosol.	
Lower explosion limit:	-	
·	not determined	
Ignition temperature:		
	not determined	
Vapour pressure:		
	(20 °C)	
	not determined	
	(50 °C)	
	not determined	
Density:	0.860 g/cm3	
	(20 °C)	
	The data given are those of the	
	active ingredient.	
Relative vapour density (air):		
	Heavier than air.	
Partitioning coefficient n-	octanol/water (log Kow):	
0	not applicable for mixtures	
Thermal decomposition:		d as prescribed/indicated.
Viscosity, kinematic:	•	·
•	(40 °C)	
	No data available.	
Explosion hazard:	not explosive	
Fire promoting properties	: not fire-propagating	
· · · · ·		
9.2. Other information	n	
Self heating ability:	It is not a material capable of	

spontaneous heating

Miscibility with water:

immiscible

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

10.2. Chemical stability

Page: 10/16 Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 11.12.2023 Version: 6.0 Date / Previous version: 17.11.2023 Previous version: 5.0 Product: ARDROX 3140, Aerosol

(ID no. 30706300/SDS_GEN_GB/EN) Date of print 12.12.2023

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

Risk of bursting. Vapours may form explosive mixture with air.

10.4. Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid direct sunlight.

10.5. Incompatible materials

Substances to avoid:

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

10.6. Hazardous decomposition products

Possible decomposition products:

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on toxicological effects

Acute toxicity

Assessment of acute toxicity: Based on available data, the classification criteria are not met.

Irritation

Assessment of irritating effects: Based on available data, the classification criteria are not met.

Respiratory/Skin sensitization

Assessment of sensitization: Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: Based on available data, the classification criteria are not met. Page: 11/16 Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 11.12.2023 Version: 6.0 Date / Previous version: 17.11.2023 Previous version: 5.0 Product: ARDROX 3140, Aerosol

(ID no. 30706300/SDS_GEN_GB/EN) Date of print 12.12.2023

Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Assessment of STOT single: Possible narcotic effects (drowsiness or dizziness).

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity: Based on available data, the classification criteria are not met.

Aspiration hazard

May also damage the lung at swallowing (aspiration hazard).

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

There are no test results available for this product. Do not allow to enter drains or waterways. The mixture has been assessed following regulation (EC) No 1272/2008 and is classified for ecotoxicological properties accordingly. See sections 2 and 3 for details.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H2O): No data available concerning biodegradation and elimination.

12.3. Bioaccumulative potential

Bioaccumulation potential: No data available.

12.4. Mobility in soil

Assessment transport between environmental compartments: Adsorption in soil: No data available.

Page: 12/16 Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 11.12.2023 Version: 6.0 Date / Previous version: 17.11.2023 Previous version: 5.0 Product: ARDROX 3140, Aerosol

(ID no. 30706300/SDS_GEN_GB/EN) Date of print 12.12.2023

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

12.6. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Dispose of the substance/product as special waste in accordance with Directive 2008/98/EC.

Waste key:

Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging:

Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14: Transport Information

Land transport

ADR

UN number or ID number:	UN1950
UN proper shipping name:	AEROSOLS
Transport hazard class(es):	2.1
Packing group:	Not applicable
Environmental hazards:	no
Special precautions for	Tunnel code: D
user:	

RID

UN number or ID number: UN1950

Page: 13/16

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 11.12.2023 Version: 6.0 Date / Previous version: 17.11.2023 Previous version: 5.0 Product: ARDROX 3140, Aerosol

(ID no. 30706300/SDS_GEN_GB/EN) Date of print 12.12.2023

UN proper shipping name: AEROSOLS Transport hazard class(es): 2.1 Packing group: Not applicable Environmental hazards: no Special precautions for None known user:

Inland waterway transport ADN

UN number or ID number:	UN1950
UN proper shipping name:	AEROSOLS
Transport hazard class(es):	2.1
Packing group:	Not applicable
Environmental hazards:	no
Special precautions for	None known
user:	

<u>Transport in inland waterway vessel</u> Not evaluated

Sea transport

IMDG

user:

UN number or ID number:	UN 1950
UN proper shipping name:	AEROSOLS
Transport hazard class(es):	2.1
Packing group:	Not applicable
Environmental hazards:	no
	Marine pollutant: NO
Special precautions for	-

Air transport

IATA/ICAO

UN number or ID number:	UN 1950
UN proper shipping name:	AEROSOLS, FLAMMABLE
Transport hazard class(es):	2.1
Packing group:	Not applicable
Environmental hazards:	No Mark as dangerous for the environment is needed
Special precautions for	None known
user:	

Page: 14/16

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 11.12.2023 Version: 6.0 Date / Previous version: 17.11.2023 Previous version: 5.0 Product: ARDROX 3140, Aerosol

(ID no. 30706300/SDS_GEN_GB/EN) Date of print 12.12.2023

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2010/75/EU of the European Parliament and of the Council of 24 November 2010 on industrial emissions (integrated pollution prevention and control) VOC content: 78.9 % VOC content: 678.5 g/l

Prohibitions, Restrictions and Authorizations

UK REACH SI, Annex XVII, Marketing and Use Restrictions Number on List: 28

UK REACH SI, Annex XVII, Marketing and Use Restrictions Number on List: 29

UK REACH SI, Annex XVII, Marketing and Use Restrictions Number on List: 3

propane, Hydrocarbons, C3-4; Petroleum gas, butane, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics, distillates (petroleum), hydrotreated heavy naphthenic,

Page: 15/16 Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 11.12.2023 Version: 6.0 Date / Previous version: 17.11.2023 Previous version: 5.0 Product: ARDROX 3140, Aerosol

(ID no. 30706300/SDS_GEN_GB/EN) Date of print 12.12.2023

Distillates (petroleum), hydrotreated heavy paraffinic, Distillates (petroleum), solvent-dewaxed heavy paraffinic

propane, Hydrocarbons, C3-4; Petroleum gas, butane, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU): Listed in above regulation: FLAMMABLE AEROSOLS 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids Category 1

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other Information

Literature and Data Sources: REACH-Regulation (EC) No. 1907/2006. CLP-Regulation (EC) No. 1272/2008.

Restricted to professional users.

	tions, including the hazard classes and the hazard statements, if mentioned	
in section 2 or 3:	The sector of the second sector should be	
Aquatic Chronic	Hazardous to the aquatic environment - chronic	
STOT SE	Specific target organ toxicity — single exposure	
Flam. Aerosol	Flammable aerosols	
Asp. Tox.	Aspiration hazard	
Flam. Liq.	Flammable liquids	
Skin Corr./Irrit.	Skin corrosion/irritation	
Eye Dam./Irrit.	Serious eye damage/eye irritation	
Repr.	Reproductive toxicity	
STOT RE	Specific target organ toxicity — repeated exposure	
H222	Extremely flammable aerosol.	
H229	Pressurized container: May burst if heated.	
H304	May be fatal if swallowed and enters airways.	
H336	May cause drowsiness or dizziness.	
H412	Harmful to aquatic life with long lasting effects.	
H226	Flammable liquid and vapour.	
H315	Causes skin irritation.	
H411	Toxic to aquatic life with long lasting effects.	
H225	Highly flammable liquid and vapour.	
H319	Causes serious eye irritation.	
H361f	Suspected of damaging fertility.	
H373	May cause damage to organs through prolonged or repeated inhalation	

Page: 16/16 Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time. Date / Revised: 11.12.2023 Version: 6.0 Date / Previous version: 17.11.2023 Previous version: 5.0 Product: ARDROX 3140, Aerosol

(ID no. 30706300/SDS_GEN_GB/EN) Date of print 12.12.2023

EUH066

exposure. Repeated exposure may cause skin dryness or cracking.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.