

CORROSION INHIBITING COMPOUNDS

COR-BAN® 27L



Product description:

CORROSION INHIBITING COMPOUND BMS 3-38B

FEATURES:

- A non-drying corrosion inhibiting compound
- ► An amber/tan color

KEY BENEFITS:

- ▶ USER SAFE
- ► NON-TOXIC
- ► LOW ODOR
- ► WIDE TEMPERATURE APPLICATIONS UP TO 280°F
- ► CONTAINS NO CHROMATES, ASBESTOS, MoS₂, OR GRAPHITE
- WITHSTANDS HIGH ULTRA VIOLET EXPOSURE IN HIGHLY CORROSIVE ENVIRONMENTS
- WITHSTANDS BRIEF EXPOSURE TO TEMPERATURES UP TO 500°F WITH LITTLE IMPACT ON IT'S CORROSION PROTECTIVE PROPERTIES.



Rev: 20063E 4-28-2021







COR-BAN® 27L



Product description:

CORROSION INHIBITING

COMPOUND BMS 3-38B

KEY BENEFITS:

- WORKS ON ANY METAL SURFACE
- ► APPROVED AS A REPLACEMENT FOR CHROMATE CONTAINING NON-CURING PASTES
- YIELDS A SMOOTH, NON-DRYING, EVEN FILM THAT YIELDS EXCELLENT CORROSION RESISTANCE
- COATS INTRICATE PARTS

SPECS:

- •Airbus CML 05-133
- •BMS 3-38B
- •CSNP038 Ty X
- •DPM 6498
- •Embraer E9447580
- •GMS 4109 Rev C
- •HMS 20-1267/2372

- •LGQP 5010E TY V
- •MEP-QPL-09-075
- •NSN: 6850-01-469-7645
- (Quart)
- •NSN: 6850-01-531-7357
- (5 oz. Tube)

- •NSN: 8030-01-531-7355
- (6 oz. Semco Cartridge)
- •SS 8689 REV 6 (-002)
- •T.O. 4S1-108-1
- •T.O. 4S1-182
- •T.O. 4W-1-61

APPLICATIONS

Apply by spatula or brush at reasonable ambient temperatures

Speed properties of Cor-Ban® 27L by preheating it to 100 - 120°F

Apply at room temperature or at elevated temperature depending on the desired type of coverage





