

COR-BAN® 35



Product description:

CORROSION INHIBITING

COMPOUND

FEATURES:

- A long lasting, high solids, low volatile, high penetration, and water displacing corrosion inhibiting compound
- Non-tacky with a light, transparent, reddish-pink tint

KEY BENEFITS:

- NON-CRACKING AND FLAKING TO -40°F (-40°C)
- LOW VOC
- DETECTABLE AND NON-SAGGING THIXOTROPIC FILM
- SOLVENT REMOVABLE
- WATER DISPLACING
- HIGH PENETRATION
- VERY LOW DRY FILM WEIGHT
- > 2000 HOURS SALT SPRAY



Rev: 20066D 5-14-2021







COR-BAN® 35



Product description:

CORROSION INHIBITING

COMPOUND

KEY BENEFITS:

- ONE AEROSOL CAN COVERS APPROXIMATELY 95 FT² (8.8 M²)
- ► 1 GALLON OF BULK MATERIAL CAN COVER APPROXIMATELY 1600 FT² (39.3 M² PER LITER)

SPECS:

- •AIMS 09-08-002 Ty II Gr 2
- •AIMS 09-08-003
- •ATR 42/ATR 72 SRM
- •BAE: AVP 2-022
- •BMS 3-23F Tyll
- •BMS 3-29
- •BMS 3-35B
- •Boeing DMS 2150
- •Bombardier BAMS 565-006 Type I and Type II
- Cessna CSNP038 Ty IVA/Class 2
- Dassault DGQT 1.7.0.0103
- •de Havilland DHMS C 4.12
- •Embraer 51-61-00 Ty I & Ty II
- •FedEx A30-51-001



- •GAC115AD
- Gulfstream GAC115AD
- •MEP 10-063
- •Mil-DTL-85054D
- •NSN: 6850-01-492-2932, 8030-01-531-7358
- (Aerosols)
- •NSN: 8030-01-615-4740 (Gallons)
- •NSN: 8030-01-659-2958 (1 Gallon)
- •NSN: 8030-01-531-7360 (5 Gallons)
- •NSN: 8030-01-615-4733 (8 oz Brush In Cap)
- •NSN: 8030-01-615-4737 (Quart)
- SIKORSKY SS 8536 Type II
- •Sukhoi RRJ0000·RE-811-2559
- •Viking VMS C4.12





COR-BAN® 35



Product description:

CORROSION INHIBITING

COMPOUND

APPLICATIONS

Apply by using conventional airless or air-operated spray equipment or by using aerosol

Apply at 1 - 1½ mils (25-38 microns) wet thickness

The **Cor-Ban® 35** aerosol can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated

Use on high profile aircraft substrates; upper edge floor beams, wheel wells, pressure deck, and center wing sections

