

### D-5026NS



#### *Product description:*

#### **AVIONIC CORROSION PREVENTIVE COMPOUND (MIL-PRF-81309H TYPE II&III, CLASS 2) GRADE CO<sub>2</sub>**

#### **FEATURES:**

- ▶ A medium to heavy duty water displacing, thin film, corrosion preventive compound

#### **KEY BENEFITS:**

- ▶ DOES NOT HARM MOST PAINTS, PLASTICS, OR INSULATION
- ▶ PREVENTS CORROSION AND DISPLACES WATER
- ▶ PROVIDES CORROSION PROTECTION FOR ASSEMBLY AS WELL AS IN-SERVICE COMPONENTS
- ▶ PROVIDES SUPERIOR PROTECTION TO AVIONIC CONNECTORS AND COMPONENTS AND HAS LUBRICATING PROPERTIES TO PREVENT FRETTING CORROSION



Rev: 20065H  
5-27-2021



For more information contact us :  
[zipchem@addevmaterials.com](mailto:zipchem@addevmaterials.com)



Part of



**ADDEV**MATERIALS

### D-5026NS



#### *Product description:*

#### **AVIONIC CORROSION PREVENTIVE COMPOUND (MIL-PRF-81309H TYPE II&III, CLASS 2) GRADE CO<sub>2</sub>**

#### **KEY BENEFITS:**

- ▶ PROTECTS ELECTRICAL CONNECTORS FROM CORRODING
- ▶ PREVENTS OXIDATION OF THE SUBSTRATE
- ▶ DOES NOT DISRUPT CONTACT BETWEEN CONNECTORS
- ▶ PROVIDES PROTECTION IN THE HARSHTEST ENVIRONMENTS
- ▶ COATING CAN WITHSTAND TEMPERATURES UP TO 105°C FOR ONLY 500 HOURS CUMULATIVE
- ▶ THE CURED FILM OF **D-5026NS** CAN WITHSTAND TEMPERATURES AS LOW AS -55°C AND AS HIGH AS 85°C CONTINUOUSLY
- ▶ USEFUL FOR INITIAL PROTECTION DURING SHIPMENT AND STORAGE AND FOR IN-SERVICE TREATMENT OF CRITICAL AREAS



For more information contact us :  
[zipchem@addevmaterials.com](mailto:zipchem@addevmaterials.com)



Part of



**ADDEV**MATERIALS

### D-5026NS



#### *Product description:*

#### **AVIONIC CORROSION PREVENTIVE COMPOUND (MIL-PRF-81309H TYPE II&III, CLASS 2) GRADE CO<sub>2</sub>**

#### **KEY BENEFITS:**

- ▶ ONE AEROSOL COVERS  
APPROXIMATELY 140 FT<sup>2</sup>

#### **SPECS:**

- AD 2002-16-03
- Boeing Alert Service Bulletin 737-24A1148
- DPM-5707-1
- Embraer E6125209
- MIL-PRF-81309H Type II & III, Class 2, Grade CO<sub>2</sub>
- NSN: 8030-01-603-2129 (Aerosol)
- NSN: 8030-01-572-8734 (Aerosol)
- Sikorsky SS 8536 Ty 1

#### **APPLICATIONS**

**D-5026NS** can be used in conjunction with the **Formit®** extensions to provide targeted spray to areas that may be difficult to reach but need to be coated

Store at 40°F-100°F (4°C-38°C)

Bulk application available as **ZC-026**



For more information contact us :  
[zipchem@addevmaterials.com](mailto:zipchem@addevmaterials.com)



Part of



**ADEV**MATERIALS