

# **Cross Check™**

## Torque Seal® Tamper-Proof Indicator Paste

#### **HANDLING**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been readand understood.
- Do not handle, store or open near an open flame, sources of heat or sources of ignition.
- Protect material from direct sunlight. Explosion-proof

#### **DIRECTIONS**

- DRY TIME: Dry to touch/handle in 30-40 minutes.
- 80% curing occurs between 48-72 hours. Completion of curing takes place between 7-10 days.
- Exposing to elevated temperature OR blowing hot air can speed up the drying/curing process.

#### **STORAGE**

• Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

#### **DISPOSAL**

 Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose ofcontents/container in accordance with local/regional/national/international regulations.

### **FEATURES**

- Tamper Proof Torque Mark
- Safe for most surfaces
- Highly visible- blue, yellow, red, green, and orange colors are fluorescent under blacklight
- Excellent adhesion
- Visually detects loose nuts & bolts
- Provides warranty protection
- Meets BOEING Specification, BMS8-45 Type II



#### PHYSICAL PROPERTIES

| Appearance / Physical State | Liquid                               |  |  |
|-----------------------------|--------------------------------------|--|--|
| Odor                        | mild                                 |  |  |
| Flash Point                 | 105.1 °F (40.6 °C)                   |  |  |
| Boiling Point / Range       | 276.98 - 485.06 °F (136.1 - 251.7 °C |  |  |
| VOC Content                 | 42.28%, 430 g/L                      |  |  |
| Vapor Density               | > 1 (air = 1)                        |  |  |
| Prop 65 Warning             | YES                                  |  |  |

#### **AVAILABLE IN**

| Color  | Net      | Cnt. | Units/ | Part # |        |
|--------|----------|------|--------|--------|--------|
|        | Contents | Type | Case   | US     | Canada |
| orange | 1 oz     | tube | 24     | 83314  | C83314 |
| green  | 1 oz     | tube | 24     | 83315  |        |
| red    | 1 oz     | tube | 24     | 83316  | C83316 |
| yellow | 1 oz     | tube | 24     | 83317  | C83317 |
| blue   | 1 oz     | tube | 24     | 83318  | C83318 |
| white  | 1 oz     | tube | 24     | 83319  | C83319 |
| pink   | 1 oz     | tube | 24     | 83320  | C83320 |
| gray   | 1 oz     | tube | 24     | 83321  |        |

