

1. IDENTIFICATION:

PRODUCT NAME: EVERLUBE 620C PRODUCT CODE: PEV620C PRODUCT USE.: Low Friction Coating HMIS CODES H F R P 2*3 1 G

Manufacturer:

EVERLUBE PRODUCTS 100 COOPER CIRCLE PEACHTREE CITY, GA 30269

EMERGENCY PHONE (24 hours): CHEMTREC - 800-424-9300 INFORMATION PHONE (8:00 a.m - 5:00 p.m EST): (770) 261-4800 NAME OF PREPARER: CHEMICAL COMMUNICATIONS COORDINATOR DATE PREPARED: 2/12/2016

2. HAZARDS INDENTIFICATION



CLASSIFICATION: Highly Flammable Liquid and Vapors - Category 2 Acute Toxicity - Category 3 Aquatic Chronic Toxicity - Category 3 Aspiration Hazard - Category 1 Carcinogenicity - Category 2 Serious Eye Damage - Category 1 Germ Cell Mutagenicity - Category 2 Reproductive Toxicity - Category 2 Skin Corrosion/Irritation - Category 1B Specific target organ toxicity, repeated exposure - Category 2 Specific target organ toxicity, single exposure - Category 1

SIGNAL WORD:

DANGER

HAZARDS STATEMENT:

H301-Toxic if swallowed H311-Toxic in contact with skin H314-Causes severe skin burns and eye damage H331-Toxic if inhaled H341-Suspected of causing genetic defects H351-Suspected of causing cancer H361-Suspected of damaging fertility or the unborn child. H370-Causes damage to organs H412-Harmful to aquatic life with long lasting effects

PRECAUTIONARY STATEMENTS:

P202-Do not handle until all safety precautions have been read and understood. P210-Keep away from heat/sparks/open flames/hot surfaces - No smoking P242-Use only non-sparking tools. P280-Wear protective gloves/eye protection/face protection.

EVERLUBE 620C Page 2 of 9

EVERLUBE[®] PRODUCTS SAFETY DATA SHEET

P403-P233-Store in well-ventilated place. Keep container tightly closed. P501-Dispose of contents/container in accordance with local/regional/national/regulation.

3. COMPOSITION/INFORMATION ON INGREDIENTS	CAS#	8 BY WT.	
METHYL ETHYL KETONE	78-93-3	25% - 30%	
ACGIH TLV: 200 ppm			
ACGIH STEL: 300 ppm			
NIOSH REL: TWA 200 ppm			
NIOSH REL: TWA 590 mg/m3			
OSHA PO: TWA 200 ppm			
OSHA PO: TWA 590 mg/m3			
OSHA PO: STEL 300 ppm			
OSHA PO STEL 885 mg/m3			
EC50 ALGAE ?100 mg/l 96 hr			
LD50 ORAL 3400.0 mg/kg (RATS)			
DC50 VAPORS 2000 PPM (RATS)			
LC50 FISH 100 mg/l 96 hr			
EC50 DAPHNIA >100 mg/l 48 hr			
ETHANOL	64-17-5	20% - 25%	
OSHA PEL 1000.000 ppm TWA			
NIOSH REL 1,000 ppm TWA			
NIOSH REL 1,900 mg/m3			
OSHA Z-1 1,000 ppm TWA			
OSHA Z-1 1,900 mg/m3			
ACGIH 1,000 ppm STEL			
LD50 ORAL 7060 mg/kg (rat)			
LC 50 INHALATION 124.7 mg/l (rat)			
LC50 FISH 15,300 mg/l 96h			
EC50 DAPHNIA 5,012mg/l 48hr			
EC50 ALGAE 275 mg/l 72 hr	1000 64 4		
ANTIMONY TRIOXIDE	1309-64-4	5% - 10%	
OSHA Z-1 0.5 mg/m3 TWA OSUA DO: 0.5 mg/m3 TWA			
OSHA PO: 0.5 mg/m3 TWA NOISH REL 0.5 mg/m3			
LD Oral Rat: $>34,600 \text{ mg/kg}$			
LC50 Fish: >1,000 mg/l 96hr			
EC50 Daphnia: >1,000 mg/l 48 hr			
PHENOL	108-95-2	0% - 5%	
ACGIH TLV-TWA 5 ppm (Skin)	100 90 2		
ACGIH TLV-TWA 19 mg/m3 (8hr)			
OSHA PEL-TWA 5 ppm (skin)			
OSHA PEL TWA 19 mg/m3 (8hr)			
LC50 Inhalation Vapor Rat 316 mg/m3 4 hr			
LD50 Dermal Rabbit 630 mg/kg			
LD50 Dermal Rat 69 mg/kg			
LD50 Oral Rat 317 mg/kg			
LC50 FISH 14-25 mg/1 48hr			
EC50 DAPHNIA 56 mg/l 48hr			
EC50 ALGAE 370 mg/l 96hr			
ISOPROPANOL	67-63-0	0% - 5%	
ACGIH TWA: 200 ppm			
ACGIH STEL: 400 ppm			
NOISH REL: 400 ppm			
NOISH REL: 980 mg/m3			
NOISH STEL: 500 ppm			
NOISH STEL: 1,225 mg/m3			
OSHA Z1 PEL: 400 ppm			

EVERLUBE PRODUCTS

OSHA Z1 PEL: 980 mg/m3 LC50 DAPHNIA 10,00 mg/l 24 hr LC50 INHALATION: 16000ppm 4hr (rat) LC50 FISH 5770-7450 mg/l 95hr LD50 ORAL RAT: 5,045 mg/kg LC50 INHALATION RAT: 16,000 ppm LD50 DERMAL RABBIT: 12,800 mg/kg 67-56-1 0% - 5% METHYL ALCOHOL OSHA PEL 200.000 ppm-TWA OSHA VPEL 200.000 ppm-TWA (Skin) OSHA VPEL 500.000 ppm-STEL (Skin) ACGIH TLV 200.000 ppm-TWA (Skin) ACHIH TLV 250.000 ppm-STEL (Skin) LC50 VAPORS 1600 ppm (rats) LD50 ORAL 1000.0 mg/kg (man EC50 ALGAE 22,000.0 mg/l 96h FISH:Mortality LC50-Bluegill-15,400.0 mg/l-95h NOEC-Oryzias Latipes-7,900 mg/1-200h EC 50- Daphnia Magn ->10,000.00 MG/L-48h METHYL ISOBUTYL KETONE 108-10-1 0% - 5% ACGIH TWA: 20 ppm ACGIH STEL: 75 ppm NIOSH REL: 50 ppm NIOSH REL: 205 mg/m3 NIOSH STEL: 75 ppm NIOSH STEL: 300 mg/m3 OSHA Z1-TWA100 ppm OSHA Z1-410 mg/m3 OSHA PO-TWA 50 ppm OSHA P0-205 mg/m3 OSHA PO-stel 75 ppm OSHA 300 mg/m3 LD50 RAT ORAL: 2080 mg/kg LD50 INHALATION RAT: >2000 PPM, 4 hr LC50 RAT INHALATION 8.L2-16.4 mg/l LC50 FISH >179 mg/l 96h EC50 AQUATIC INVERTEBRATES >200 mg/l 48h EC50 ALGAE 400 mg/l 95h

4. First Aid Measures

Eyes:

With eyelids open, immediately flush eyes with lots of lukewarm water for at least 30 minutes. Get immediate medical assistance.

Skin:

Wash the skin thoroughly with plenty of water for at least 15 minutes, using a mild and non-abrasive soap. Cold water may be used.

Ingestion:

Never give anything by mouth if the victim is semi-conscious, unconscious, or convulsing.

Inhalation:

Evacuate to fresh air and administer artificial respiration if breathing stopped. Obtain medical aid.

5. Fire Fighting Measures

Flammable Properties:



Flash Point (Degree F): 16F
Flash Point Method TCC
Explosive Limits:
 Upper explosive limit: 36.0
 Lower explosive limit: 1.2

Hazardous Combustion Products:

Carbon, Sulfur, Antimony, or their compounds

Extinguishing Media:

CO2, foam, dry chemical or halon

Firefighting Procedures:

Fire-Fighters should wear self-contained breathing apparatus and full protective equipment.

Extinguish all nearby sources of ignition.

6. Accidental Release Measures

Small Spill:

Eliminate all sources of ignition, provide ventilation, contain spill, and absorb with inert absorbent.

Wear appropriate breathing apparatus (if applicable) and protective clothing.

Use only non-sparking tools and equipment.

Large Spill:

Remove by mechanical means and place in containers.

Use only non-sparking tools and equipment.

Environmental Precautions:

Prevent product or wash waters from entering the water system or sewers.

US regulations require reporting spills of this material that could reach any surface waters. In Canada, report to the applicable provincial environment ministry.

7. Handling and Storage

Handling:

Avoid breathing dust/fume/gas/mist/vapors/spray.

Do not get in eyes, on skin, or on clothing.

Wash contaminated clothing thoroughly after handling.

Wash skin thoroughly (with soap and water) after handling.

Storage:

Store in a cool, dry well ventilated place, away from incompatible materials.

Store in a closed/sealed container.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:



Mixture, see section 3

Engineering Controls:

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below the threshold limit values.

Use explosion-proof electrical/ventilating/lighting equipment.

Prevent the product or the wash waters from entering the water system or sewers.

Personal Protective Equipment:



Respiratory Protection:

In case of inadequate ventilation, wear respirator protection. Use NIOSH/MSHA approved Cartridge Respirator or Mask to keep airborne mists and concentrations below the time weighted threshold limit values.

Skin Protection:

Wear protective gloves (eg Neoprene or Nitrile) for skin protection.

Eye Protection:

Wear eye protection/face protection. Contact lenses should not be worn without goggles.

9. Physical and Chemical Properties

Flammability (solid, gas):	Data not available
Boiling Point	148.5F
Melting Point	Data not available
VOC	632 grams/liter
Freezing Point	Data not available
Flash Point	16F
Vapor Pressure	Data not available
Vapor Density	Heavier than air.
Solubility in Water	Slightly Soluble
Density	9.1 lb/gl
Evaporation Rate	Faster than n-Butyl Acetate.
Explosive Limits:	
Upper Explosive Limit:	36.0
Lower Explosive Limit:	1.2
Specific Gravity	1.09286
РН:	None known
Volatile (% by Weight)	60%
Appearance and Odor	Gray/Black liquid, organic solvent odor
Odor Threshold	Not applicable
Viscosity	Not applicable
Partition Coefficient:	Data not available
Decomposition Temperature:	Data not available
Autoignition temperature:	Data not available

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid): Stable under normal conditions.



Incompatibility:

Oxidizers, Strong Acids or Alkalies.

Hazardous Decomposition Products:

Irritating and/or toxic fumes including the following may be released: None known

Hazardous Polymerization:

Will not occur.

11. Toxicological Information

Acute Toxicity Values: Mixture, see section 3 - Hazardous Ingredients

Germ Cell Mutagenicity:

Suspected of causing genetic defects

Chronic/Carcinogenicity:

IARC (International Agency for Research of Cancer): Group 2B-Possibly carcinogenic to humans

NTP (National Toxicology Program): Not listed as a carcinogen

Reproductive Toxicity:

Product contains chemical(s) suspected of damaging fertility/unborn child

STOT-single exposure:

If inhaled may cause drowsiness or dizziness

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard:

None known

Routes of Exposure:

Skin contact, skin absorption, eye contact, inhalation

12. Ecological Information

Environmental Fate:

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Canadian and U.S. regulations require that environmental and/or other agencies be notified of a spill incident. The spill area must be cleaned and restored to the original condition or to the satisfaction of authorities.

Environmental Toxicity:

Data not available

Persistence and Degradability:

Data not available

Bioaccumulative Potential:

Data not available

Mobility in Soil



Data not available

Other Adverse Effects:

None known

13. Disposal Considerations

Disposal Methods:

Dispose of contents/container to: A licensed waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licensed waste disposal site with approval of environment authority.

14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

UN Number: UN 1263

UN Shipping Name: PAINT RELATED MATERIAL

PAINI KELAIED MAIEKIAL

Transport Hazard Class:

Class 3

Packing Group: Group II

ENVIRONMENTAL HAZARDS:

Marine Pollutant: None known

Special Precautions for User: None known

15. Regulatory Information

U.S. Federal Regulations:

OSHA: OSHA Regulated

TSCA:

ALL COMPONENTS OF THIS PRODUCT ARE ON THE TSCA INVENTORY OR ARE EXTINCT FROM REQUIREMENTS

CERCLA: SARA Hazard Category:

Section 313:

IF THIS MATERIAL HAS ANY COMPONENTS THAT ARE REPORTABLE UNDER SARA 313 THEY ARE SHOWN IN THE FOLLOWING LISTING. IF THE LISTING IS BLANK, THERE ARE NO REPORTABLE COMPONENTS.



CAS #

8 BY WT.

ETHANOL	64-17-5	20% - 25%
ANTIMONY TRIOXIDE	1309-64-4	5% - 10%
PHENOL	108-95-2	0% - 5%
METHYL ALCOHOL	67-56-1	0% - 5%

FRANK DODD SECTION 1502:

ALL COMPONENTS OF THIS PRODUCT COMPLY WITH TITLE 15 OF THE US CONSUMER FINANCIAL PROTECTION ACT, DODD-FRANK ACT SECTION 1502 (CONFLICT MINERALS ACT).

State Regulations:

COMPONENT

California Prop 65:

This product contains a chemical known to the State of California to cause cancer.

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

International Regulations:

WHMIS:

B2, D2A, D2B,

CEPA (Canadian Environmental Protection Act)

ALL INGREDIENTS ARE CEPA APPROVED FOR IMPORT TO CANADA. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED PRODUCTS REGULATION (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

EINECS (European Inventory of Existing Chemical List)

ALL COMPONENTS OF THIS PRODUCT ARE INCLUDED ON THE EUROPEAN INVENTORY OF EXISTING CHEMICALS LIST

16. Other Information

Date of Preparation: 2/12/2016

KEY/LEGEND

ACGIH: American Conference of Governmental Industrial Hygienists ADR: International Carriage of Dangerous Goods by Road RID: International Carriage of Dangerous Goods by Rail CAS: Chemical Abstracts Service CERCLA: Comprehensive Environmental Response, Compensation, & Liability Act DOT: Department of Transportation HMIS: Hazardous Materials Identification System IATA: International Air Transport Association ICAO: International Civil Aviation Organization IDL: Immediately Dangerous to Life IMDG: International Maritime Dangerous Goods IMO: International Maritime Organization LC: Lethal Concentration LD: Lethal Dose NIOSH: National Institute for Occupational Safety & Health OSHA: Occupational Safety & Health Administration PPM: Parts Per Million

EVERLUBE[®] PRODUCTS SAFETY DATA SHEET

REL: Recommended Exposure Limit SARA: Superfund Amendments and Reauthorization Act STEL: Short-term Exposure Limits STOT: Specific Target Organ Toxicity TLV: Threshold Limit Value TSCA: Toxic Substances Control Act TWA: Time Weighted Average VOC: Volatile Organic Compounds WHMIS: Workplace Hazardous Materials Information System

Manufacturer Disclaimer:

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION AND RECOMMENDATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION OR OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. HOWEVER, IT IS THE USERS RESPONSIBILITY TO DETERMINE SAFETY, TOXICITY, AND SUITABLITY FOR HIS OWN USE OF THE PRODUCT. EVERLUBE PRODUCTS ASSUMES NO RESPONSIBILITY. THE CUSTOMER OR RECIPIENT OF THIS SDS SHOULD ENSURE THAT THE INFORMATION CONTAINED IN THIS SDS IS MADE AVAILABLE TO ALL EMPLOYEES OR OTHER PERSONS WHOM HE KNOWS OR BELIEVES WILL USE THIS MATERIAL

www.everlubeproducts.com