



Safety Data Sheet

Page 1 of 11

LOCTITE SF 7471 PRIMER known as Loctite(R) Locquic(R)
Primer T

SDS No. : 153665

V001.3

Revision: 12.10.2022

printing date: 15.06.2023

SECTION 1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product name: LOCTITE SF 7471 PRIMER known as Loctite(R) Locquic(R) Primer T

Intended use: Primer

Supplier:
Henkel New Zealand Ltd
2 Allens Rd
Auckland, 2013
New Zealand
Phone: +64 (9) 272-6710

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER 0800 243 622

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classified as hazardous according to the criteria of the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017

Classified as Dangerous Goods according to NZS 5433: 2012 and the Land Transport Rule: Dangerous Goods 2005.

GHS Classification:

Hazard Class

Aerosol
Serious eye irritation
Target Organ Systemic Toxicant -
Single exposure
Acute hazards to the aquatic
environment
Chronic hazards to the aquatic
environment

Hazard Category

Category 1
Category 2A
Category 3

Category 2

Category 3

Target organ

Central nervous system

Hazard pictogram:



Signal word:

Danger

Hazard statement(s):	H222 Extremely flammable aerosol. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H401 Toxic to aquatic life. H412 Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.
Precautionary Statement(s):	
Prevention:	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing gas/mist/spray. P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear eye protection/face protection.
Response:	P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.
Storage:	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

General chemical description: Mixture

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
acetone	67-64-1	50- < 70 %
Propan-2-ol	67-63-0	1- < 10 %
2,2'-[(4-methylphenyl)imino]bisethanol	3077-12-1	0.1- < 1 %
benzothiazole-2-thiol	149-30-4	0.1- < 1 %
non hazardous ingredients~		30- <= 60 %

SECTION 4 FIRST AID MEASURES

Ingestion:	Do not induce vomiting. Get medical attention. Keep individual calm. If conscious, drink plenty of water.
Skin:	Immediately flush skin with plenty of water (using soap, if available).

Eyes: Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time.

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Foam, dry chemical or carbon dioxide.

Decomposition products in case of fire: Oxides of sulfur.
Oxides of nitrogen.
Irritating organic vapours.
Oxides of carbon.

Particular danger in case of fire: Vapors may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.

Special protective equipment for fire-fighters: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Ensure adequate ventilation.
Wear protective equipment.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Store in a partly filled, closed container until disposal.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Ensure adequate ventilation.
Remove all sources of ignition.

SECTION 7. HANDLING AND STORAGE

Conditions for safe storage: Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.
Store only in the original container.
Keep away from sources of ignition.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Workplace exposure standards:**

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Ceiling	STEL (ppm)	STEL (mg/m3)
ACETONE 67-64-1		500	1,185	-	-	-
ACETONE		-	-	-	1,000	2,375
ISOPROPYL ALCOHOL 67-63-0		400	983	-	-	-
ISOPROPYL ALCOHOL		-	-	-	500	1,230

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
Acetone 67-64-1 [ACETONE]	acetone	Urine	Sampling time: End of shift.	50 mg/l	NZ BEI		

Engineering controls: Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

Eye protection: Wear protective glasses.

Skin protection: Chemical resistant, impermeable gloves.
Use protective gloves.
Recommended gloves include butyl rubber and neoprene.

Respiratory protection: If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: amber, yellow
Aerosol
Odor: Acetone
Specific gravity: 0.7953
Flash point: -8 °C (17.6 °F)
(Tagliabue closed cup) Estimated
Vapor pressure: 172 mm hg
Approximately
VOC content: 8.31 % 106 g/l

SECTION 10. STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

Incompatible materials: Strong oxidizing agents.

Hazardous decomposition products: Oxides of sulfur.
Irritating organic vapours.
Oxides of nitrogen.
Oxides of carbon.

Hazardous polymerization: Will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

Health Effects:

Ingestion: Not expected under normal conditions of use.
May cause central nervous system effects, such as headache, nausea, vomiting, abdominal pain, dizziness, confusion, and breathing difficulties.
May cause gastrointestinal tract irritation if swallowed.

Skin: May cause mild skin irritation.
Repeated exposure may cause skin dryness or cracking.
Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Solvent action can dry and defat the skin, causing the skin to crack, leading to dermatitis.

Eyes: Causes serious eye irritation.
Symptoms may include severe irritation, pain, tearing, blurred vision.
Vapors may irritate eyes. Contact with eyes will cause irritation.

Inhalation: May cause irritation to nose and throat.
Vapours may cause drowsiness and dizziness.
Central nervous system depression, including dizziness, drowsiness, fatigue, nausea, headache, unconsciousness.
May cause respiratory tract irritation.
Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.

Aggravated med. condition:

Eye, skin, and respiratory disorders.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
acetone 67-64-1	LD50 LC50 LD50	5,800 mg/kg 76 mg/l > 15,688 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	not specified not specified Draize Test
Propan-2-ol 67-63-0	LD50 LD50	5,840 mg/kg 12,870 mg/kg	oral dermal		rat rabbit	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)
2,2'-(4-methylphenyl)imino]bisethanol 3077-12-1	LD50 LD50	959 mg/kg > 2,000 mg/kg	oral dermal		rat rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)
benzothiazole-2-thiol 149-30-4	LD50 LC50 LD50	2,830 mg/kg > 1,270 mg/l > 7,940 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	not specified not specified not specified

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
acetone 67-64-1	not irritating		guinea pig	not specified
Propan-2-ol 67-63-0	slightly irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2,2'-[(4- methylphenyl)imino]biset hanol 3077-12-1	not irritating	24 h	rabbit	not specified

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
acetone 67-64-1	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Propan-2-ol 67-63-0	Category II		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2,2'-[(4- methylphenyl)imino]biset hanol 3077-12-1	Category 1 (irreversible effects on the eye)		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
acetone 67-64-1	not sensitising	Guinea pig maximisa- tion test	guinea pig	not specified
Propan-2-ol 67-63-0	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
2,2'-[(4- methylphenyl)imino]biset hanol 3077-12-1	sensitising	Mouse local lymphnod- e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
benzothiazole-2-thiol 149-30-4	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
benzothiazole-2-thiol 149-30-4	sensitising	Guinea pig maximisa- tion test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
acetone 67-64-1	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay	with and without with and without without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
acetone 67-64-1	negative	oral: drinking water		mouse	not specified
Propan-2-ol 67-63-0	negative negative	bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay	with and without with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Propan-2-ol 67-63-0	negative	intraperitoneal		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
benzothiazole-2-thiol 149-30-4	negative	intraperitoneal		mouse	Micronucleus assay

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
acetone 67-64-1	NOAEL=900 mg/kg	oral: drinking water	13 wdaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Propan-2-ol 67-63-0		inhalation: vapour	at least 104 w6 h/d, 5 d/w	rat	OECD Guideline 451 (Carcinogenicity Studies)
benzothiazole-2-thiol 149-30-4	NOAEL=375 mg/kg	oral: gavage	13 weeks5 days/week	rat	not specified
benzothiazole-2-thiol 149-30-4	LOAEL=750 mg/kg	oral: gavage	13 weeks5 days/week	rat	not specified

SECTION 12. ECOLOGICAL INFORMATION

General ecological information:

Do not empty into drains, soil or bodies of water.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
acetone 67-64-1	LC50	8,120 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
acetone 67-64-1	EC50	8,800 mg/l	Daphnia	48 h	Daphnia pulex	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
acetone 67-64-1	NOEC	530 mg/l	Algae	8 d	Microcystis aeruginosa	DIN 38412-09
acetone 67-64-1	EC10	1,000 mg/l	Bacteria	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)
Propan-2-ol 67-63-0	LC50	> 9,640 - 10,000 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Propan-2-ol 67-63-0	EC50	> 1,000 mg/l	Algae	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	NOEC	1,000 mg/l	Algae	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propan-2-ol 67-63-0	EC50	> 1,000 mg/l	Bacteria	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
2,2'-[(4-methylphenyl)imino]bisethanol 3077-12-1	LC50	> 100 mg/l	Fish	96 h	Cyprinus carpio	OECD Guideline 203 (Fish, Acute Toxicity Test)
2,2'-[(4-methylphenyl)imino]bisethanol 3077-12-1	EC50	48 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2,2'-[(4-methylphenyl)imino]bisethanol 3077-12-1	EC50	> 100 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-[(4-methylphenyl)imino]bisethanol 3077-12-1	NOEC	100 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-[(4-methylphenyl)imino]bisethanol 3077-12-1	EC50	> 1,000 mg/l	Bacteria	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
benzothiazole-2-thiol 149-30-4	LC50	0.73 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
benzothiazole-2-thiol 149-30-4	NOEC	0.041 mg/l	Fish	89 d	Oncorhynchus mykiss	other guideline:
benzothiazole-2-thiol 149-30-4	EC50	0.71 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
benzothiazole-2-thiol 149-30-4	EC50	0.5 mg/l	Algae	72 h	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
benzothiazole-2-thiol 149-30-4	NOEC	0.066 mg/l	Algae	72 h	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
benzothiazole-2-thiol 149-30-4	EC50	3,301 mg/l	Bacteria	3 h	activated sludge	OECD Guideline 209 (Activated

Sludge, Respiration
Inhibition Test)**Persistence and degradability:**

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
acetone 67-64-1	readily biodegradable	aerobic	81 - 92 %	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
Propan-2-ol 67-63-0	readily biodegradable	aerobic	70 - 84 %	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)
2,2'-[(4-methylphenyl)imino]bisethanol 3077-12-1	not readily biodegradable.	aerobic	1.5 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
benzothiazole-2-thiol 149-30-4		aerobic	2.5 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
acetone 67-64-1	-0.24					OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Propan-2-ol 67-63-0	0.05					OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
2,2'-[(4-methylphenyl)imino]bisethanol 3077-12-1	2				35 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
benzothiazole-2-thiol 149-30-4		< 8	6 Weeks	Cyprinus carpio		other guideline:
benzothiazole-2-thiol 149-30-4	2.34 - 2.5					not specified

SECTION 13. DISPOSAL CONSIDERATIONS**Waste disposal of product:** Dispose of in accordance with local and national regulations.**Disposal for uncleaned package:** Packaging that cannot be cleaned are to be disposed of in the same manner as the product.**SECTION 14. TRANSPORT INFORMATION****Land Transport:**

UN no.: 1950
 Proper shipping name: AEROSOLS
 Class or division: 2.1
 Packing group:

Marine transport IMDG:

UN no.: 1950
 Proper shipping name: AEROSOLS
 Class or division: 2.1
 Packing group:

EmS: F-D ,S-U
Seawater pollutant: -

Air transport IATA:

UN no.: 1950
Proper shipping name: Aerosols, flammable
Class or division: 2.1
Packing group:
Packing instructions (passenger) 203
Packing instructions (cargo) 203

SECTION 15. REGULATORY INFORMATION

HSNO Approval Number: HSR002515

Approved Handler: Refer to the certified handler requirements in the Health and Safety at Work (Hazardous Substances) Regulations 2017

Site and Storage: Refer to the site and storage requirements for this Group Standard.

NZIoC: Compliant for NZIOC

SECTION 16. OTHER INFORMATION

Abbreviations/acronyms: STEL - Short term exposure limit
TWA - Time weighted average
HSNO - Hazardous Substances and New Organisms

Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 2,11,16

Date of previous issue: 13.09.2017

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel New Zealand Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel New Zealand Limited concerning the properties of the material.

The information contained in this Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel New Zealand Limited assumes no legal responsibility for reliance upon same. Henkel New Zealand Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by Government statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

