



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 18

LOCTITE SF 7063 400ML EGFD

SDS No. : 179512
V010.0

Revision: 05.05.2022

printing date: 06.05.2022

Replaces version from: 06.09.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE SF 7063 400ML EGFD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Industrial Cleaning Agents

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Aerosol

Category 1

H222 Extremely flammable aerosol.

H229 Pressurized container: May burst if heated.

Skin irritation

Category 2

H315 Causes skin irritation.

Specific target organ toxicity - single exposure

Category 3

H336 May cause drowsiness or dizziness.

Target organ: Central nervous system

Chronic hazards to the aquatic environment

Category 2

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

cyclohexane

n-Hexane

Signal word:**Danger****Hazard statement:**

H222 Extremely flammable aerosol.
 H229 Pressurized container: May burst if heated.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statement:

For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with national regulation.
 P251 Do not pierce or burn, even after use.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P211 Do not spray on an open flame or other ignition source.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P102 Keep out of reach of children.

**Precautionary statement:
Prevention**

P273 Avoid release to the environment.
 P261 Avoid breathing spray.

**Precautionary statement:
Response**

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

2.3. Other hazards

The aerosol container is under pressure. Do not expose to high temperatures.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration $\geq 0,1\%$ and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration \geq the concentration limit that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0 921-024-6 01-2119475514-35	50- 100 %	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411		
Ethanol 64-17-5 200-578-6 01-2119457610-43	10- < 20 %	Eye Irrit. 2, H319 Flam. Liq. 2, H225	Eye Irrit. 2; H319; C >= 50 %	
Methylal 109-87-5 203-714-2 01-2119664781-31	10- 20 %	Flam. Liq. 2, H225		
cyclohexane 110-82-7 203-806-2 01-2119463273-41	5- < 10 %	Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Flam. Liq. 2, H225 Skin Irrit. 2, H315	M acute = 1 M chronic = 1	EU OEL
n-Hexane 110-54-3 203-777-6 01-2119480412-44	1- < 3 %	Flam. Liq. 2, H225 Repr. 2, H361f Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	STOT RE 2; H373; C >= 5 %	EU OEL
Carbon dioxide 124-38-9 204-696-9	5- < 10 %	Press. Gas H280		EU OEL

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to Detergent Regulation 648/2004/EC

> 30 % aliphatic hydrocarbons

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

Vapors may cause drowsiness and dizziness.

Prolonged or repeated contact may cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

Foam, extinguishing powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Wear protective equipment.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

Wipe up using absorbent material.

Store in a partly filled, closed container until disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Keep away from sources of ignition - no smoking.

Vapours should be extracted to avoid inhalation.

Use only in well-ventilated areas.

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Refer to Technical Data Sheet

7.3. Specific end use(s)

Industrial Cleaning Agents

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethanol 64-17-5 [ETHANOL]	1.000	1.920	Time Weighted Average (TWA):		EH40 WEL
Dimethoxymethane 109-87-5 [DIMETHOXYMETHANE]	1.000	3.160	Time Weighted Average (TWA):		EH40 WEL
Dimethoxymethane 109-87-5 [DIMETHOXYMETHANE]	1.250	3.950	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Cyclohexane 110-82-7 [CYCLOHEXANE]	100	350	Time Weighted Average (TWA):		EH40 WEL
Cyclohexane 110-82-7 [CYCLOHEXANE]	200	700	Time Weighted Average (TWA):	Indicative	ECTLV
Cyclohexane 110-82-7 [CYCLOHEXANE]	300	1.050	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Carbon dioxide 124-38-9					
Carbon dioxide 124-38-9 [CARBON DIOXIDE]	5.000	9.150	Time Weighted Average (TWA):		EH40 WEL
Carbon dioxide 124-38-9 [CARBON DIOXIDE]	5.000	9.000	Time Weighted Average (TWA):	Indicative	ECTLV
Carbon dioxide 124-38-9 [CARBON DIOXIDE]	15.000	27.400	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
n-Hexane 110-54-3 [N-HEXANE]	20	72	Time Weighted Average (TWA):		EH40 WEL
n-Hexane 110-54-3 [N-HEXANE]	20	72	Time Weighted Average (TWA):	Indicative	ECTLV

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethanol 64-17-5 [ETHANOL]	1.000		Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Dimethoxymethane 109-87-5 [METHYLAL]	1.000	3.100	Time Weighted Average (TWA):		IR_OEL
Cyclohexane 110-82-7 [CYCLOHEXANE]	200	700	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Cyclohexane 110-82-7 [CYCLOHEXANE]	200	700	Time Weighted Average (TWA):	Indicative	ECTLV
Carbon dioxide 124-38-9					
Carbon dioxide 124-38-9 [CARBON DIOXIDE]	5.000	9.000	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Carbon dioxide	5.000	9.000	Time Weighted Average	Indicative	ECTLV

124-38-9 [CARBON DIOXIDE]			(TWA):		
n-Hexane 110-54-3 [N-HEXANE]	20	72	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
n-Hexane 110-54-3 [N-HEXANE]			Skin designation:	Can be absorbed through the skin.	IR_OEL
n-Hexane 110-54-3 [N-HEXANE]	20	72	Time Weighted Average (TWA):	Indicative	ECTLV

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Ethanol 64-17-5	aqua (freshwater)		0,96 mg/l				
Ethanol 64-17-5	aqua (marine water)		0,79 mg/l				
Ethanol 64-17-5	aqua (intermittent releases)		2,75 mg/l				
Ethanol 64-17-5	sewage treatment plant (STP)		580 mg/l				
Ethanol 64-17-5	sediment (freshwater)				3,6 mg/kg		
Ethanol 64-17-5	sediment (marine water)				2,9 mg/kg		
Ethanol 64-17-5	Soil				0,63 mg/kg		
Ethanol 64-17-5	oral				380 mg/kg		
Dimethoxymethane 109-87-5	aqua (freshwater)		14,577 mg/l				
Dimethoxymethane 109-87-5	aqua (marine water)		1,4577 mg/l				
Dimethoxymethane 109-87-5	sediment (freshwater)				13,135 mg/kg		
Dimethoxymethane 109-87-5	sediment (marine water)				1,3135 mg/kg		
Dimethoxymethane 109-87-5	Soil				4,6538 mg/kg		
Dimethoxymethane 109-87-5	Sewage treatment plant		10000 mg/l				
cyclohexane 110-82-7	aqua (freshwater)		0,207 mg/l				
cyclohexane 110-82-7	aqua (marine water)		0,207 mg/l				
cyclohexane 110-82-7	aqua (intermittent releases)		0,207 mg/l				
cyclohexane 110-82-7	sediment (freshwater)				16,68 mg/kg		
cyclohexane 110-82-7	sediment (marine water)				16,68 mg/kg		
cyclohexane 110-82-7	Soil				3,38 mg/kg		
cyclohexane 110-82-7	sewage treatment plant (STP)		3,24 mg/l				
cyclohexane 110-82-7	Air						
cyclohexane 110-82-7	Predator						no potential for bioaccumulation

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Workers	dermal	Long term exposure - systemic effects		773 mg/kg	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Workers	inhalation	Long term exposure - systemic effects		2035 mg/m3	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	dermal	Long term exposure - systemic effects		699 mg/kg	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	inhalation	Long term exposure - systemic effects		608 mg/m3	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	General population	oral	Long term exposure - systemic effects		699 mg/kg	
Ethanol 64-17-5	Workers	dermal	Long term exposure - systemic effects		343 mg/kg	
Ethanol 64-17-5	Workers	inhalation	Long term exposure - systemic effects		950 mg/m3	
Ethanol 64-17-5	General population	dermal	Long term exposure - systemic effects		206 mg/kg	
Ethanol 64-17-5	General population	inhalation	Long term exposure - systemic effects		114 mg/m3	
Ethanol 64-17-5	General population	oral	Long term exposure - systemic effects		87 mg/kg	
Dimethoxymethane 109-87-5	Workers	dermal	Long term exposure - systemic effects		17,9 mg/kg	
Dimethoxymethane 109-87-5	Workers	inhalation	Long term exposure - systemic effects		126,6 mg/m3	
Dimethoxymethane 109-87-5	General population	oral	Long term exposure - systemic effects		18,1 mg/kg	
Dimethoxymethane 109-87-5	General population	inhalation	Long term exposure - systemic effects		31,5 mg/m3	
Dimethoxymethane 109-87-5	General population	dermal	Long term exposure - systemic effects		18,1 mg/kg	
cyclohexane 110-82-7	Workers	inhalation	Acute/short term exposure - local effects		700 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	Workers	inhalation	Acute/short term exposure - systemic effects		700 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	Workers	inhalation	Long term exposure - systemic effects		700 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	Workers	inhalation	Long term exposure - local effects		700 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	Workers	dermal	Long term exposure - systemic effects		2016 mg/kg	no potential for bioaccumulation
cyclohexane 110-82-7	General population	inhalation	Acute/short term exposure - systemic effects		412 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	General population	inhalation	Acute/short term exposure - local effects		412 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	General population	dermal	Long term exposure - systemic effects		1186 mg/kg	no potential for bioaccumulation
cyclohexane 110-82-7	General population	oral	Long term exposure -		59,4 mg/kg	no potential for bioaccumulation

			systemic effects			
cyclohexane 110-82-7	General population	inhalation	Long term exposure - systemic effects		206 mg/m3	no potential for bioaccumulation
cyclohexane 110-82-7	General population	inhalation	Long term exposure - local effects		206 mg/m3	no potential for bioaccumulation
n-Hexane 110-54-3	General population	inhalation	Long term exposure - systemic effects		16 mg/m3	
n-Hexane 110-54-3	Workers	dermal	Long term exposure - systemic effects		11 mg/kg	
n-Hexane 110-54-3	General population	dermal	Long term exposure - systemic effects		5,3 mg/kg	
n-Hexane 110-54-3	Workers	inhalation	Long term exposure - systemic effects		75 mg/m3	
n-Hexane 110-54-3	General population	oral	Long term exposure - systemic effects		4 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Use filter A-P2 if vapours/aerosols occur which may be inhaled.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	aerosol
Delivery form	aerosol
Colour	colourless
Odor	hydrocarbons
Initial boiling point	-78 °C (-108.4 °F)None
Explosive limits	
lower	0,8 %(V);
upper	15 %(V);
	Upper/lower explosion limit
Flash point	-18 °C (0.4 °F)
pH	Product is non-soluble (in water)., Not applicable
Solubility (qualitative) (Solvent: Water)	Not miscible
Solubility (qualitative) (Solvent: Acetone)	Miscible
Vapour pressure (20 °C (68 °F))	440 hPa
Density (20 °C (68 °F))	0,742 g/cm3 None

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity**10.1. Reactivity**

Strong oxidizing agents.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None if used for intended purpose.

SECTION 11: Toxicological information

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Ethanol 64-17-5	LD50	10.470 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Methylal 109-87-5	LD50	6.423 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
cyclohexane 110-82-7	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
n-Hexane 110-54-3	LD50	16.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Ethanol 64-17-5	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Methylal 109-87-5	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
cyclohexane 110-82-7	LD50	> 2.000 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
n-Hexane 110-54-3	LD50	> 2.000 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LC50	> 25,2 mg/l	vapour	4 h	rat	not specified
Ethanol 64-17-5	LC50	124,7 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Methylal 109-87-5	LC50	15.000 mg/l	vapour	4 h	rat	not specified
cyclohexane 110-82-7	LC50	> 32,880 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
n-Hexane 110-54-3	LC50	> 31,86 mg/l	vapour	4 h	rat	not specified

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Ethanol 64-17-5	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
n-Hexane 110-54-3	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Ethanol 64-17-5	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
cyclohexane 110-82-7	slightly irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
n-Hexane 110-54-3	not irritating		rabbit	not specified

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Ethanol 64-17-5	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Ethanol 64-17-5	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
cyclohexane 110-82-7	not sensitising	Buehler test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
n-Hexane 110-54-3	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Ethanol 64-17-5	negative	bacterial reverse mutation assay (e.g Ames test)			OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Ethanol 64-17-5	negative	in vitro mammalian chromosome aberration test	without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Ethanol 64-17-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
cyclohexane 110-82-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
cyclohexane 110-82-7	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
n-Hexane 110-54-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
n-Hexane 110-54-3	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Ethanol 64-17-5	not carcinogenic					Expert judgement
n-Hexane 110-54-3	not carcinogenic	inhalation: vapour	2 y 6 h/d; 5 d/w	mouse	female	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Ethanol 64-17-5	NOAEL P 13.800 mg/kg	Two generation study	oral: unspecified	mouse	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
cyclohexane 110-82-7	NOAEL F1 7000 ppm	two- generation study	inhalation: vapour	rat	equivalent or similar to OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
n-Hexane 110-54-3	NOAEL P 9000 ppm NOAEL F1 3000 ppm NOAEL F2 3000 ppm	Two generation study	inhalation: vapour	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
cyclohexane 110-82-7		inhalation: vapour	13-14 w 6 h/d, 5 d/w	mouse	EPA OPPTS 870.3465 (90-Day Inhalation Toxicity)
n-Hexane 110-54-3	NOAEL 568 mg/kg	oral: gavage	90 d 5 d/w	rat	not specified
n-Hexane 110-54-3	NOAEL 500 ppm	inhalation: vapour	90 d 6 h/d; 5 d/w	mouse	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
cyclohexane 110-82-7	0,41 mm ² /s	40 °C	not specified	
n-Hexane 110-54-3	0,45 mm ² /s	25 °C	not specified	

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	LL50	11,4 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethanol 64-17-5	LC50	14.200 mg/l	96 h	Pimephales promelas	EPA-660 (Methods for Acute Toxicity Tests with Fish, Macroinvertebrates and Amphibians)
Ethanol 64-17-5	NOEC	250 mg/l	120 h	Danio rerio	OECD Guideline 212 (Fish, Short-term Toxicity Test on Embryo and Sac-Fry Stages)
Methylal 109-87-5	LC50	6.990 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
cyclohexane 110-82-7	LC50	4,53 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
n-Hexane 110-54-3	LC50	> 1 - 10 mg/l	96 h	not specified	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	EL50	3 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethanol 64-17-5	EC50	5.012 mg/l	48 h	Ceriodaphnia dubia	other guideline:
Methylal 109-87-5	EC50	> 500 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
cyclohexane 110-82-7	EC50	0,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
n-Hexane 110-54-3	EC50	2,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	NOEC	0,17 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Ethanol 64-17-5	NOEC	9,6 mg/l	9 d	Daphnia magna	not specified

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	EL50	> 30 - 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	NOELR	3 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethanol 64-17-5	EC50	275 mg/l	72 h	Chlorella vulgaris	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethanol 64-17-5	EC10	11,5 mg/l	72 h	Chlorella vulgaris	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methylal 109-87-5	EC10	> 500 mg/l	96 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
cyclohexane 110-82-7	EC50	9,317 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
cyclohexane 110-82-7	NOEC	0,95 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
n-Hexane 110-54-3	EC50	> 1 - 10 mg/l	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethanol 64-17-5	IC50	> 1.000 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Methylal 109-87-5	EC10	3.000 mg/l	17 h		DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
cyclohexane 110-82-7	IC50	29 mg/l	15 h	other:	not specified
n-Hexane 110-54-3	EC50	> 1 - 10 mg/l	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	readily biodegradable	aerobic	98 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Ethanol 64-17-5	readily biodegradable	aerobic	80 - 85 %	30 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Methylal 109-87-5	not readily biodegradable.	aerobic	> 0 - < 60 %	28 d	OECD 301 A - F
cyclohexane 110-82-7	readily biodegradable	aerobic	77 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
n-Hexane 110-54-3	readily biodegradable	aerobic	81 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
cyclohexane 110-82-7	167			Pimephales promelas	QSAR (Quantitative Structure Activity Relationship)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Ethanol 64-17-5	-0,35	24 °C	not specified
cyclohexane 110-82-7	3,44	25 °C	QSAR (Quantitative Structure Activity Relationship)
n-Hexane 110-54-3	4	20 °C	other guideline:

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane 92128-66-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Ethanol 64-17-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Methylal 109-87-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
cyclohexane 110-82-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
n-Hexane 110-54-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

14 06 03 Other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number

ADR	1950
RID	1950
ADN	1950
IMDG	1950
IATA	1950

14.2. UN proper shipping name

ADR	AEROSOLS
RID	AEROSOLS
ADN	AEROSOLS
IMDG	AEROSOLS (Solvent Naphtha (Petroleum), Light Aromatic)
IATA	Aerosols, flammable

14.3. Transport hazard class(es)

ADR	2.1
RID	2.1
ADN	2.1
IMDG	2.1
IATA	2.1

14.4. Packing group

ADR
RID
ADN
IMDG
IATA

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode: (D)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	95 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapor.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361f Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.