

ISO-9001 Registered Quality System. ISO-21469 Compliant. Sales, Service & Distribution Center Newark, NJ 07105 Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center Toledo, OH 43605 Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE MO-LITH No. 2

DESCRIPTION

LUBRIPLATE Mo-Lith No. 2 is exactly what the name indicates -- a moly-lithium lubricant – containing Technical Fine Molybdenum Disulfide. The use of moly has been widely acclaimed by various members in the lubricant field: however, unless the correct amount is used, it has little affect on the end result. Likewise, the base grease that carries the moly must be of premium quality or the benefits are not forthcoming. In LUBRIPLATE Mo-Lith No. 2, we have compounded the optimum percentage of moly for the greatest performance.

APPLICATIONS

Recommended as a primary friction barrier lubricant

ADVANTAGES

- Anti-wear/extreme pressure reinforced by the addition of Molybdenum Disulfide (MoS2)
- ⇒ Non-corrosive
- ⇒ High water resistance

STORAGE RECOMMENDATIONS

- ⇒ Products should be stored between 40°F-120°F
- ⇒ Products should be stored in a dry covered environment
- \Rightarrow Products should not be stored in warm, direct sunlight
- ⇒ Improper storage conditions can significantly alter the shelf life of the product. Such conditions would include temperature, moisture, open containers, etc.

Typical Test Data

	TYPICAL RESULTS*
	Lithium
ASTM D-217	265 to 295
	2
ASTM D566	350°F/177°C
ASTM D-2161	600
ASTM D-445	112
Visual	Steel Gray
	METHOD ASTM D-217 ASTM D566 ASTM D-2161 ASTM D-445

⇒ Contains Molybdenum Disulfide

PACKAGING AVAILABLE

Carton, 12/16 oz. Plastic Tubs	L0180-004
Carton, 4/6 lb. Plastic Tubs	L0180-005
35 lb. Pail	L0180-035
120 lb. Quarter Size Drum	L0180-039
430 lb. Full Size Drum	L0180-040
Carton, 40/14 oz. Cartridges	L0180-098



Part No.