

Safety data sheet

Page: 1/13

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 29.01.2021

Version: 2.0

Date previous version: 28.01.2019

Previous version: 1.0

Product: **Naftoseal MC-238 B-1/2 Base**

(ID no. 30737643/SDS_GEN_GB/EN)

Date of print 15.09.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Naftoseal MC-238 B-1/2 Base

UFI: SAPA-E33H-G004-9Q2D

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Sealant

Not recommended use: Uses other than recommended

1.3. Details of the supplier of the safety data sheet

Company:

BASF SE
67056 Ludwigshafen
GERMANY

Contact address:

BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
UNITED KINGDOM

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 29.01.2021

Version: 2.0

Date previous version: 28.01.2019

Previous version: 1.0

Product: **Naftoseal MC-238 B-1/2 Base**

(ID no. 30737643/SDS_GEN_GB/EN)

Date of print 15.09.2022

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 3

H412 Harmful to aquatic life with long lasting effects.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elementsGlobally Harmonized System, EU (GHS)

Hazard Statement:

H412

Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P273

Avoid release to the environment.

Precautionary Statements (Disposal):

P501

Dispose of contents and container to hazardous or special waste collection point.

2.3. Other hazardsAccording to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

SECTION 3: Composition/Information on Ingredients**3.1. Substances**

Not applicable

3.2. MixturesChemical nature

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 29.01.2021

Version: 2.0

Date previous version: 28.01.2019

Previous version: 1.0

Product: **Naftoseal MC-238 B-1/2 Base**

(ID no. 30737643/SDS_GEN_GB/EN)

Date of print 15.09.2022

fillers, organic solvent

Hazardous ingredients (GHS)

according to Regulation (EC) No. 1272/2008

| Liquid polysulphide polymer with thiol end groups (MW>1800)

Content (W/W): >= 50 % - < 75 % Aquatic Chronic 3

CAS Number: 68611-50-7 H412

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures**4.1. Description of first aid measures**

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:

If symptoms persist, seek medical advice. Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution.

On ingestion:

Do not induce vomiting. Rinse mouth thoroughly with water, seek medical attention. If adverse health effects develop seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Symptomatic treatment (decontamination, vital functions).

Antidote: No known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

5.2. Special hazards arising from the substance or mixture

Endangering substances: carbon oxides, sulfur oxides

Advice: Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

5.3. Advice for fire-fighters

Special protective equipment:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Avoid breathing vapours. Keep away from sources of ignition.

Ensure adequate ventilation. Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not discharge into the subsoil/soil. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. The relevant fire protection measures should be noted.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Further information on storage conditions: Keep container dry. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep away from heat.

Storage stability:

Storage temperature: < 26 °C

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

No occupational exposure limits known.

Biological limit values (BLV)

No data available.

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 29.01.2021

Version: 2.0

Date previous version: 28.01.2019

Previous version: 1.0

Product: **Naftoseal MC-238 B-1/2 Base**

(ID no. 30737643/SDS_GEN_GB/EN)

Date of print 15.09.2022

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. (Gas filter EN 14387 A)

Hand protection:

Chemical resistant protective gloves (EN 374)

nitrile rubber (NBR) - 0.4 mm coating thickness

Performance level 6, corresponding to a breakthrough time of >480 min according to EN ISO 374-1

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Chemical resistant protective clothing according to DIN EN 13034 (Type 6)

General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible.

Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

Environmental exposure controls

For information regarding environmental exposure controls, see Section 6.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form:	paste
Colour:	beige
Odour:	characteristic
pH value:	substance/mixture is non-soluble (in water)
Melting point:	not determined
onset of boiling:	not determined
Flash point:	> 95 °C
Flammability:	hardly combustible
Lower explosion limit:	not determined

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 29.01.2021

Version: 2.0

Date previous version: 28.01.2019

Previous version: 1.0

Product: **Naftoseal MC-238 B-1/2 Base**

(ID no. 30737643/SDS_GEN_GB/EN)

Date of print 15.09.2022

Ignition temperature:	240 °C	
Vapour pressure:	(20 °C) not determined	
	(50 °C) not determined	
Density:	1.480 g/cm ³ (20 °C)	(DIN 51757)
Solubility in water:	immiscible	
Self ignition:	not self-igniting	
Viscosity, kinematic:	(40 °C) not determined	
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	

9.2. Other information

Self heating ability: It is not a substance capable of spontaneous heating.

Miscibility with water:
immiscible

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

10.4. Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid direct sunlight. Avoid heat.

10.5. Incompatible materials

Substances to avoid:

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

10.6. Hazardous decomposition products

Possible decomposition products:

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 29.01.2021

Version: 2.0

Date previous version: 28.01.2019

Previous version: 1.0

Product: **Naftoseal MC-238 B-1/2 Base**

(ID no. 30737643/SDS_GEN_GB/EN)

Date of print 15.09.2022

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Based on available Data, the classification criteria are not met.

Irritation

Assessment of irritating effects:

The liquid splashed in the eyes may cause irritation and reversible damage. Based on available Data, the classification criteria are not met.

Respiratory/Skin sensitization

Assessment of sensitization:

Based on available Data, the classification criteria are not met.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available Data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

Based on available Data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on available Data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

Based on available Data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on available Data, the classification criteria are not met.

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 29.01.2021

Version: 2.0

Date previous version: 28.01.2019

Previous version: 1.0

Product: **Naftoseal MC-238 B-1/2 Base**

(ID no. 30737643/SDS_GEN_GB/EN)

Date of print 15.09.2022

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on available Data, the classification criteria are not met.

Aspiration hazard

No aspiration hazard expected.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

There are no test results available for this product. Do not allow to enter drains or waterways. The mixture has been assessed following regulation (EC) No 1272/2008 and is classified for ecotoxicological properties accordingly. See sections 2 and 3 for details.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H₂O):

No data available concerning biodegradation and elimination.

12.3. Bioaccumulative potential

Bioaccumulation potential:

No data available.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: No data available.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

12.6. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Observe national and local legal requirements.

Waste key:

Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging:

Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14: Transport Information

Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

RID

Not classified as a dangerous good under transport regulations

UN number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

UN number: Not applicable

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 29.01.2021

Version: 2.0

Date previous version: 28.01.2019

Previous version: 1.0

Product: **Naftoseal MC-238 B-1/2 Base**

(ID no. 30737643/SDS_GEN_GB/EN)

Date of print 15.09.2022

UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

	Not classified as a dangerous good under transport regulations
UN number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Air transport

IATA/ICAO

	Not classified as a dangerous good under transport regulations
UN number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

14.1. UN number

See corresponding entries for "UN number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 29.01.2021

Version: 2.0

Date previous version: 28.01.2019

Previous version: 1.0

Product: **Naftoseal MC-238 B-1/2 Base**

(ID no. 30737643/SDS_GEN_GB/EN)

Date of print 15.09.2022

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation:	Not evaluated
Shipment approved:	Not evaluated
Pollution name:	Not evaluated
Pollution category:	Not evaluated
Ship Type:	Not evaluated

SECTION 15: Regulatory Information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):
Listed in above regulation: no

15.2. Chemical Safety Assessment

Chemical Safety Assessment not required

SECTION 16: Other Information

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Aquatic Chronic
H412

Hazardous to the aquatic environment - chronic
Harmful to aquatic life with long lasting effects.

Abbreviations

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 29.01.2021

Version: 2.0

Date previous version: 28.01.2019

Previous version: 1.0

Product: **Naftoseal MC-238 B-1/2 Base**

(ID no. 30737643/SDS_GEN_GB/EN)

Date of print 15.09.2022

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

Safety data sheet

Page: 1/16

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.08.2022

Version: 2.0

Date previous version: 27.05.2019

Previous version: 1.0

Date / First version: 27.05.2019

Product: **Naftoseal MC-238 B-1/2 Hardener**

(ID no. 30738099/SDS_GEN_GB/EN)

Date of print 15.09.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Naftoseal MC-238 B-1/2 Hardener

UFI: KWN2-916X-J00G-VNRE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Hardener for coating materials or adhesives for industrial or professional use

Not recommended use: Uses other than recommended

1.3. Details of the supplier of the safety data sheet

Company:

BASF SE
67056 Ludwigshafen
GERMANY

Contact address:

BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
UNITED KINGDOM

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.08.2022

Version: 2.0

Date previous version: 27.05.2019

Previous version: 1.0

Date / First version: 27.05.2019

Product: **Naftoseal MC-238 B-1/2 Hardener**

(ID no. 30738099/SDS_GEN_GB/EN)

Date of print 15.09.2022

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Acute Tox. 4 (oral)	H302 Harmful if swallowed.
Skin Corr./Irrit. 2	H315 Causes skin irritation.
Eye Dam./Irrit. 2	H319 Causes serious eye irritation.
STOT RE 1	H372 Causes damage to organs through prolonged or repeated exposure.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Pictogram:



Signal Word:

Danger

Hazard Statement:

H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H372	Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P260	Do not breathe dust or mist.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P270	Do not eat, drink or smoke when using this product.
P264	Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.08.2022

Version: 2.0

Date previous version: 27.05.2019

Previous version: 1.0

Date / First version: 27.05.2019

Product: **Naftoseal MC-238 B-1/2 Hardener**

(ID no. 30738099/SDS_GEN_GB/EN)

Date of print 15.09.2022

P314	Get medical advice/attention if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P301 + P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P337 + P313	If eye irritation persists: Get medical attention.
P332 + P313	If skin irritation occurs: Get medical attention.
P330	Rinse mouth
P362 + P364	Take off contaminated clothing and wash it before reuse.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Labeling of special preparations (GHS):

| EUH208: May produce an allergic reaction. Contains: phthalic anhydride

| Hazard determining component(s) for labelling: manganese dioxide

2.3. Other hazards

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

inorganic compounds, organic compounds

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.08.2022

Version: 2.0

Date previous version: 27.05.2019

Previous version: 1.0

Date / First version: 27.05.2019

Product: **Naftoseal MC-238 B-1/2 Hardener**

(ID no. 30738099/SDS_GEN_GB/EN)

Date of print 15.09.2022

Hazardous ingredients (GHS)

| manganese dioxide

Content (W/W): $\geq 30\%$ - $< 50\%$	Acute Tox. 4 (Inhalation - dust)
CAS Number: 1313-13-9	Acute Tox. 4 (oral)
EC-Number: 215-202-6	STOT RE (Central nervous system) 1
REACH registration number: 01-2119452801-43	H372, H302 + H332

| sodium hydroxide

Content (W/W): $\geq 0.5\%$ - $< 1\%$	Met. Corr. 1
CAS Number: 1310-73-2	Skin Corr./Irrit. 1A
EC-Number: 215-185-5	Eye Dam./Irrit. 1
REACH registration number: 01-2119457892-27	H290, H314
INDEX-Number: 011-002-00-6	<u>Specific concentration limit:</u>
	Skin Corr./Irrit. 1A: $\geq 5\%$
	Skin Corr./Irrit. 1B: $2 - < 5\%$
	Skin Corr./Irrit. 2: $0.5 - < 2\%$
	Eye Dam./Irrit. 2: $0.5 - < 2\%$

| phthalic anhydride

Content (W/W): $\geq 0.3\%$ - $< 0.5\%$	Acute Tox. 4 (oral)
CAS Number: 85-44-9	Skin Corr./Irrit. 2
EC-Number: 201-607-5	Eye Dam./Irrit. 1
REACH registration number: 01-2119457017-41	Resp. Sens. 1
INDEX-Number: 607-009-00-4	Skin Sens. 1
	STOT SE 3 (irr. to respiratory syst.)
	H318, H315, H302, H334, H317, H335

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.08.2022

Version: 2.0

Date previous version: 27.05.2019

Previous version: 1.0

Date / First version: 27.05.2019

Product: **Naftoseal MC-238 B-1/2 Hardener**

(ID no. 30738099/SDS_GEN_GB/EN)

Date of print 15.09.2022

On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

On ingestion:

Summon medical aid without delay. Do not induce vomiting due to aspiration hazard. Rinse mouth immediately with water. Keep at rest.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Eye irritation, allergic symptoms, skin irritation, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Symptomatic treatment (decontamination, vital functions).

Antidote: No known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

5.2. Special hazards arising from the substance or mixture

Endangering substances: carbon oxides

Advice: Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

5.3. Advice for fire-fighters

Special protective equipment:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.08.2022

Version: 2.0

Date previous version: 27.05.2019

Previous version: 1.0

Date / First version: 27.05.2019

Product: **Naftoseal MC-238 B-1/2 Hardener**

(ID no. 30738099/SDS_GEN_GB/EN)

Date of print 15.09.2022

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not discharge into the subsoil/soil. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. The relevant fire protection measures should be noted.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container dry. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep away from heat.

Storage stability:

Storage temperature: < 26 °C

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.08.2022

Version: 2.0

Date previous version: 27.05.2019

Previous version: 1.0

Date / First version: 27.05.2019

Product: **Naftoseal MC-238 B-1/2 Hardener**

(ID no. 30738099/SDS_GEN_GB/EN)

Date of print 15.09.2022

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

85-44-9: phthalic anhydride	TWA value 4 mg/m ³ (WEL/EH 40 (UK)) STEL value 12 mg/m ³ (WEL/EH 40 (UK)) Ceiling limit value/factor: 15 min
1310-73-2: sodium hydroxide	STEL value 2 mg/m ³ (WEL/EH 40 (UK)) Ceiling limit value/factor: 15 min
1313-13-9: manganese dioxide	TWA value 0.5 mg/m ³ (WEL/EH 40 (UK)) Measured as: manganese (Mn) TWA value 0.2 mg/m ³ (OEL (EU)), Inhalable fraction Measured as: manganese (Mn) indicative TWA value 0.05 mg/m ³ (OEL (EU)), Respirable fraction Measured as: manganese (Mn) indicative TWA value 0.05 mg/m ³ (WEL/EH 40 (UK)), Respirable fraction Measured as: manganese (Mn)

Biological limit values (BLV)

No data available.

Components with PNEC

85-44-9: phthalic anhydride	freshwater: 1 mg/l marine water: 0.1 mg/l intermittent release: 5.6 mg/l STP: 10 mg/l sediment (freshwater): 3.8 mg/kg sediment (marine water): 0.38 mg/kg soil: 0.173 mg/kg
1313-13-9: manganese dioxide	freshwater: 0.00014 mg/l marine water: 0.000014 mg/l sediment (freshwater): 0.037 mg/kg

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.08.2022

Version: 2.0

Date previous version: 27.05.2019

Previous version: 1.0

Date / First version: 27.05.2019

Product: **Naftoseal MC-238 B-1/2 Hardener**

(ID no. 30738099/SDS_GEN_GB/EN)

Date of print 15.09.2022

sediment (marine water): 0.0037 mg/kg

soil: 0.028 mg/kg

STP: 100 mg/l

intermittent release: 0.00074 mg/l

Components with DNEL

85-44-9: phthalic anhydride

worker: Long-term exposure- systemic effects, dermal: 10 mg/kg

worker: Long-term exposure- systemic effects, Inhalation: 32.3 mg/m3

consumer: Long-term exposure- systemic effects, dermal: 5 mg/kg

consumer: Long-term exposure- systemic effects, Inhalation: 8.6 mg/m3

consumer: Long-term exposure- systemic effects, oral: 5 mg/kg

1310-73-2: sodium hydroxide

worker: Long-term exposure - local effects, Inhalation: 1.0 mg/m3

1313-13-9: manganese dioxide

worker: Long-term exposure- systemic effects, Inhalation: 0.2 mg/m3

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Personal protective equipment

Respiratory protection:

Respiratory protection required if exposure limit (if available) may be exceeded (Combination filter EN 14387 AB)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

nitrile rubber (NBR) - 0.4 mm coating thickness

butyl rubber gloves - material thickness: 0.5 mm

Performance level 6, corresponding to a breakthrough time of >480 min according to EN ISO 374-1

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Chemical resistant protective clothing according to DIN EN 13034 (Type 6)

General safety and hygiene measures

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.08.2022

Version: 2.0

Date previous version: 27.05.2019

Previous version: 1.0

Date / First version: 27.05.2019

Product: **Naftoseal MC-238 B-1/2 Hardener**

(ID no. 30738099/SDS_GEN_GB/EN)

Date of print 15.09.2022

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

Environmental exposure controls

For information regarding environmental exposure controls, see Section 6.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form:	liquid	
Colour:	black	
Odour:	odourless	
pH value:		
	substance/mixture is non-soluble (in water)	
Melting point:	not determined	
onset of boiling:	not determined	
Flash point:	> 99 °C	
Flammability:	hardly combustible	
Lower explosion limit:	not determined	
Ignition temperature:	not determined	
Vapour pressure:	(20 °C) not determined	
	(50 °C) not determined	
Density:	1.590 g/cm ³ (20 °C)	(DIN 51757)
Solubility in water:	insoluble	
Viscosity, dynamic:	40,000 - 200,000 mPa*s (< 25 °C) Brookfield	
Viscosity, kinematic:	(40 °C) not determined	
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	

9.2. Other information

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.08.2022

Version: 2.0

Date previous version: 27.05.2019

Previous version: 1.0

Date / First version: 27.05.2019

Product: **Naftoseal MC-238 B-1/2 Hardener**

(ID no. 30738099/SDS_GEN_GB/EN)

Date of print 15.09.2022

Self heating ability: It is not a substance capable of spontaneous heating.

Miscibility with water: immiscible

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

10.4. Conditions to avoid

Avoid direct sunlight. Avoid heat.

10.5. Incompatible materials

Substances to avoid:

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

10.6. Hazardous decomposition products

Possible decomposition products:

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Of moderate toxicity after single ingestion.

| *Information on: phthalic anhydride*

| *Experimental/calculated data:*

| *LD50 rat (oral): 1,530 mg/kg*

Irritation

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.08.2022

Version: 2.0

Date previous version: 27.05.2019

Previous version: 1.0

Date / First version: 27.05.2019

Product: **Naftoseal MC-238 B-1/2 Hardener**

(ID no. 30738099/SDS_GEN_GB/EN)

Date of print 15.09.2022

Assessment of irritating effects:

Eye contact causes irritation. Skin contact causes irritation.

Respiratory/Skin sensitization

Assessment of sensitization:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on available data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Repeated exposure to small quantities may affect certain organs.

Aspiration hazard

No aspiration hazard expected.

SECTION 12: Ecological Information

12.1. Toxicity

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.08.2022

Version: 2.0

Date previous version: 27.05.2019

Previous version: 1.0

Date / First version: 27.05.2019

Product: **Naftoseal MC-238 B-1/2 Hardener**

(ID no. 30738099/SDS_GEN_GB/EN)

Date of print 15.09.2022

Assessment of aquatic toxicity:

There are no test results available for this product. Do not allow to enter drains or waterways. The mixture has been assessed following regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H₂O):

No data available concerning biodegradation and elimination.

12.3. Bioaccumulative potential

Bioaccumulation potential:

No data available.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: No data available.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

12.6. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Do not discharge into drains/surface waters/groundwater.

Observe national and local legal requirements.

Dispose of the substance/product as special waste in accordance with Directive 2008/98/EC.

Waste key:

Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging:

Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.08.2022

Version: 2.0

Date previous version: 27.05.2019

Previous version: 1.0

Date / First version: 27.05.2019

Product: **Naftoseal MC-238 B-1/2 Hardener**

(ID no. 30738099/SDS_GEN_GB/EN)

Date of print 15.09.2022

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14: Transport Information

Land transport

ADR

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

RID

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Inland waterway transport

ADN

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

Transport in inland waterway vessel

Not evaluated

Sea transport

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.08.2022

Version: 2.0

Date previous version: 27.05.2019

Previous version: 1.0

Date / First version: 27.05.2019

Product: **Naftoseal MC-238 B-1/2 Hardener**

(ID no. 30738099/SDS_GEN_GB/EN)

Date of print 15.09.2022

IMDG

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Air transport

IATA/ICAO

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.08.2022

Version: 2.0

Date previous version: 27.05.2019

Previous version: 1.0

Date / First version: 27.05.2019

Product: **Naftoseal MC-238 B-1/2 Hardener**

(ID no. 30738099/SDS_GEN_GB/EN)

Date of print 15.09.2022

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2010/75/EU of the European Parliament and of the Council of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

VOC content: 0.2 %

Paints and varnishes - Determination of volatile organic compound (VOC) content - Part 1: Difference method - Method 1

VOC content: 3.0 g/l

Paints and varnishes - Determination of volatile organic compound (VOC) content - Part 1: Difference method - Method 1

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 46, 3, 75

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):
Listed in above regulation: no

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

Chemical Safety Assessment not required

SECTION 16: Other Information

Literature and Data Sources: REACH-Regulation (EC) No. 1907/2006. CLP-Regulation (EC) No. 1272/2008.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Acute Tox.

Acute toxicity

Skin Corr./Irrit.

Skin corrosion/irritation

Eye Dam./Irrit.

Serious eye damage/eye irritation

STOT RE

Specific target organ toxicity — repeated exposure

Met. Corr.

Corrosive to metals

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 22.08.2022

Version: 2.0

Date previous version: 27.05.2019

Previous version: 1.0

Date / First version: 27.05.2019

Product: **Naftoseal MC-238 B-1/2 Hardener**

(ID no. 30738099/SDS_GEN_GB/EN)

Date of print 15.09.2022

Resp. Sens.	Respiratory sensitization
Skin Sens.	Skin sensitization
STOT SE	Specific target organ toxicity — single exposure
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H372	Causes damage to organs (Central nervous system) through prolonged or repeated exposure.
H302 + H332	Harmful if swallowed or if inhaled
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.