

Safety data sheet

Page: 1/15

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2023

Version: 3.1

Date previous version: 12.12.2022

Previous version: 3.0

Date / First version: 08.05.2019

Product: **Naftoseal MC-650 B-1 Base**

(ID no. 30691244/SDS_GEN_GB/EN)

Date of print 11.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Naftoseal MC-650 B-1 Base

UFI: UWWA-RAR6-600S-R395

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Sealant

Not recommended use: Uses other than recommended

1.3. Details of the supplier of the safety data sheet

Company:

BASF SE
67056 Ludwigshafen
GERMANY

Contact address:

BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
UNITED KINGDOM

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2023

Version: 3.1

Date previous version: 12.12.2022

Previous version: 3.0

Date / First version: 08.05.2019

Product: **Naftoseal MC-650 B-1 Base**

(ID no. 30691244/SDS_GEN_GB/EN)

Date of print 11.05.2023

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Eye Dam./Irrit. 2

H319 Causes serious eye irritation.

Aquatic Chronic 3

H412 Harmful to aquatic life with long lasting effects.

Flam. Liq. 3

H226 Flammable liquid and vapour.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Pictogram:



Signal Word:

Warning

Hazard Statement:

H226

Flammable liquid and vapour.

H319

Causes serious eye irritation.

H412

Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P273

Avoid release to the environment.

P280

Wear protective gloves, protective clothing and eye protection or face protection.

P240

Ground and bond container and receiving equipment.

P233

Keep container tightly closed.

P243

Take action to prevent static discharges.

P241

Use explosion-proof electrical, ventilating and lighting equipment.

P242

Use non-sparking tools.

P264

Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313

If eye irritation persists: Get medical attention.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P370 + P378

In case of fire: Use water spray for extinction.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2023

Version: 3.1

Date previous version: 12.12.2022

Previous version: 3.0

Date / First version: 08.05.2019

Product: **Naftoseal MC-650 B-1 Base**

(ID no. 30691244/SDS_GEN_GB/EN)

Date of print 11.05.2023

Precautionary Statements (Storage):

P403 + P235 Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste collection point.

2.3. Other hazards

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

fillers, organic compounds, polymers, organic solvent, pigment

Hazardous ingredients (GHS)

Liquid polysulphide polymer with thiol end groups (MW>1800)

Content (W/W): >= 50 % - < 75 %	Aquatic Chronic 3
CAS Number: 68611-50-7	H412

ethyl acetate

Content (W/W): >= 3 % - < 5 %	Flam. Liq. 2
CAS Number: 141-78-6	Eye Dam./Irrit. 2
EC-Number: 205-500-4	STOT SE 3 (drowsiness and dizziness)
REACH registration number: 01-2119475103-46	H225, H319, H336
INDEX-Number: 607-022-00-5	EUH066

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2023

Version: 3.1

Date previous version: 12.12.2022

Previous version: 3.0

Date / First version: 08.05.2019

Product: **Naftoseal MC-650 B-1 Base**

(ID no. 30691244/SDS_GEN_GB/EN)

Date of print 11.05.2023

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

On ingestion:

Do not induce vomiting. Rinse mouth thoroughly with water, seek medical attention. If adverse health effects develop seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Eye irritation, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Symptomatic treatment (decontamination, vital functions).

Antidote: No known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

5.2. Special hazards arising from the substance or mixture

Endangering substances: sulfur oxides, carbon oxides

Advice: Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2023

Version: 3.1

Date previous version: 12.12.2022

Previous version: 3.0

Date / First version: 08.05.2019

Product: **Naftoseal MC-650 B-1 Base**

(ID no. 30691244/SDS_GEN_GB/EN)

Date of print 11.05.2023

5.3. Advice for fire-fighters

Special protective equipment:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not discharge into the subsoil/soil. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2023

Version: 3.1

Date previous version: 12.12.2022

Previous version: 3.0

Date / First version: 08.05.2019

Product: **Naftoseal MC-650 B-1 Base**

(ID no. 30691244/SDS_GEN_GB/EN)

Date of print 11.05.2023

heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: tinned carbon steel (Tinplate), Carbon steel (Iron), Stainless steel 1.4301 (V2), Polypropylene (PP), Polyethylenetherephthalate (PET), Low density polyethylene (LDPE), High density polyethylene (HDPE), Stove-lacquer C222A/C221A, Stove-lacquer NOVOCAN S-G 500, Stove-lacquer Vitalure 745, Stove-lacquer Valspar HXR008F red, Stove-lacquer KNS L-5X, Stove-lacquer EHD0022, Stove-lacquer 79/14/3 (Müller/CH), Stove-lacquer R 78433, Stove-lacquer RDL 50, Aluminium

Further information on storage conditions: Keep container dry. Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions.

Storage stability:

Storage temperature: < 26 °C

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

141-78-6: ethyl acetate

TWA value 734 mg/m³ ; 200 ppm (WEL/EH 40 (UK))

STEL value 1,468 mg/m³ ; 400 ppm (WEL/EH 40 (UK))

Ceiling limit value/factor: 15 min

Biological limit values (BLV)

No data available.

Components with PNEC

141-78-6: ethyl acetate

freshwater: 0.24 mg/l

marine water: 0.024 mg/l

intermittent release: 1.65 mg/l

STP: 650 mg/l

sediment (freshwater): 1.15 mg/kg

sediment (marine water): 0.115 mg/kg

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2023

Version: 3.1

Date previous version: 12.12.2022

Previous version: 3.0

Date / First version: 08.05.2019

Product: **Naftoseal MC-650 B-1 Base**

(ID no. 30691244/SDS_GEN_GB/EN)

Date of print 11.05.2023

soil: 0.148 mg/kg

oral (secondary poisoning): 0.2 mg/kg

Components with DNEL

141-78-6: ethyl acetate

worker: Long-term exposure - systemic and local effects, Inhalation: 734 mg/m³

worker: Long-term exposure- systemic effects, dermal: 63 mg/kg

worker: Short-term exposure - systemic and local effects, Inhalation: 1468 mg/m³

consumer: Long-term exposure- systemic effects, dermal: 37 mg/kg

consumer: Long-term exposure - systemic and local effects, Inhalation: 367 mg/m³

consumer: Long-term exposure- systemic effects, oral: 4.5 mg/kg

consumer: Short-term exposure - systemic and local effects, Inhalation: 734 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Personal protective equipment

Respiratory protection:

Respiratory protection required if exposure limit (if available) may be exceeded (Gas filter EN 14387 A)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

chloroprene rubber (CR) - 0.5 mm coating thickness

butyl rubber gloves - material thickness: 0.5 mm

nitrile rubber (NBR) - 0.4 mm coating thickness

Performance level 6, corresponding to a breakthrough time of >480 min according to EN ISO 374-1

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Chemical resistant protective clothing according to DIN EN 13034 (Type 6)

General safety and hygiene measures

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2023

Version: 3.1

Date previous version: 12.12.2022

Previous version: 3.0

Date / First version: 08.05.2019

Product: **Naftoseal MC-650 B-1 Base**

(ID no. 30691244/SDS_GEN_GB/EN)

Date of print 11.05.2023

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

Environmental exposure controls

For information regarding environmental exposure controls, see Section 6.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form:	liquid	
Colour:	brown	
Odour:	solvent-like	
Odour threshold:	not determined	
pH value:	substance/mixture is non-soluble (in water)	
Melting point:	not determined	
onset of boiling:	> 250 °C	(calculated)
Flash point:	48 °C	(ISO 2719)
Flammability:	Flammable liquid and vapour.	
Lower explosion limit:	not determined	
Ignition temperature:	460 °C	
Vapour pressure:	(20 °C) not determined	
	(50 °C) not determined	
Density:	1.590 g/cm ³ (20 °C)	
Relative vapour density (air):	Heavier than air.	
Solubility in water:	insoluble	
Partitioning coefficient n-octanol/water (log Kow):	not applicable for mixtures	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, kinematic:	(40 °C) not determined	
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2023

Version: 3.1

Date previous version: 12.12.2022

Previous version: 3.0

Date / First version: 08.05.2019

Product: **Naftoseal MC-650 B-1 Base**

(ID no. 30691244/SDS_GEN_GB/EN)

Date of print 11.05.2023

9.2. Other information

Self heating ability: It is not a material capable of spontaneous heating

Miscibility with water: immiscible

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

10.4. Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid heat. Avoid direct sunlight.

10.5. Incompatible materials

Substances to avoid:

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

10.6. Hazardous decomposition products

Possible decomposition products:

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Based on available data, the classification criteria are not met.

Irritation

Assessment of irritating effects:

Not irritating to the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Eye contact causes irritation.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2023

Version: 3.1

Date previous version: 12.12.2022

Previous version: 3.0

Date / First version: 08.05.2019

Product: **Naftoseal MC-650 B-1 Base**

(ID no. 30691244/SDS_GEN_GB/EN)

Date of print 11.05.2023

Respiratory/Skin sensitization

Assessment of sensitization:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on available data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on available data, the classification criteria are not met.

Aspiration hazard

No aspiration hazard expected.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2023

Version: 3.1

Date previous version: 12.12.2022

Previous version: 3.0

Date / First version: 08.05.2019

Product: **Naftoseal MC-650 B-1 Base**

(ID no. 30691244/SDS_GEN_GB/EN)

Date of print 11.05.2023

There are no test results available for this product. Do not allow to enter drains or waterways. The mixture has been assessed following regulation (EC) No 1272/2008 and is classified for ecotoxicological properties accordingly. See sections 2 and 3 for details.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H₂O):

No data available concerning biodegradation and elimination.

12.3. Bioaccumulative potential

Bioaccumulation potential:

No data available.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: No data available.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

12.6. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Do not discharge into drains/surface waters/groundwater.

Observe national and local legal requirements.

Dispose of the substance/product as special waste in accordance with Directive 2008/98/EC.

Waste key:

Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging:

Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2023

Version: 3.1

Date previous version: 12.12.2022

Previous version: 3.0

Date / First version: 08.05.2019

Product: **Naftoseal MC-650 B-1 Base**

(ID no. 30691244/SDS_GEN_GB/EN)

Date of print 11.05.2023

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14: Transport Information

Land transport

ADR

UN number or ID number: UN1133
UN proper shipping name: ADHESIVES
Transport hazard class(es): 3
Packing group: III
Environmental hazards: no
Special precautions for user: Tunnel code: D/E

RID

UN number or ID number: UN1133
UN proper shipping name: ADHESIVES
Transport hazard class(es): 3
Packing group: III
Environmental hazards: no
Special precautions for user: None known

Inland waterway transport

ADN

UN number or ID number: UN1133
UN proper shipping name: ADHESIVES
Transport hazard class(es): 3
Packing group: III
Environmental hazards: no
Special precautions for user: None known

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

UN number or ID number: UN 1133

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2023

Version: 3.1

Date previous version: 12.12.2022

Previous version: 3.0

Date / First version: 08.05.2019

Product: **Naftoseal MC-650 B-1 Base**

(ID no. 30691244/SDS_GEN_GB/EN)

Date of print 11.05.2023

UN proper shipping name: ADHESIVES
Transport hazard class(es): 3
Packing group: III
Environmental hazards: no
Marine pollutant: NO

Special precautions for user:

Air transport

IATA/ICAO

UN number or ID number: UN 1133
UN proper shipping name: ADHESIVES
Transport hazard class(es): 3
Packing group: III
Environmental hazards: No Mark as dangerous for the environment is needed
Special precautions for user: None known

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2023

Version: 3.1

Date previous version: 12.12.2022

Previous version: 3.0

Date / First version: 08.05.2019

Product: **Naftoseal MC-650 B-1 Base**

(ID no. 30691244/SDS_GEN_GB/EN)

Date of print 11.05.2023

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2010/75/EU of the European Parliament and of the Council of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

VOC content:	6.3 %	Standard Practice for Determining Volatile Organic Compound (VOC) Content of Paints and Related Coatings - Method 1
--------------	-------	--

VOC content:	102.0 g/l	Standard Practice for Determining Volatile Organic Compound (VOC) Content of Paints and Related Coatings - Method 1
--------------	-----------	--

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):
Listed in above regulation: Flammable liquids, Categories 2 or 3 not covered by P5a and P5b

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

Chemical Safety Assessment not required

SECTION 16: Other Information

Literature and Data Sources: REACH-Regulation (EC) No. 1907/2006. CLP-Regulation (EC) No. 1272/2008.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Eye Dam./Irrit.	Serious eye damage/eye irritation
Aquatic Chronic	Hazardous to the aquatic environment - chronic
Flam. Liq.	Flammable liquids
STOT SE	Specific target organ toxicity — single exposure
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.
H225	Highly flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 04.04.2023

Version: 3.1

Date previous version: 12.12.2022

Previous version: 3.0

Date / First version: 08.05.2019

Product: **Naftoseal MC-650 B-1 Base**

(ID no. 30691244/SDS_GEN_GB/EN)

Date of print 11.05.2023

national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

Safety data sheet

Page: 1/18

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Naftoseal MC-650 B-1 Härter

UFI: 54CG-F46K-F007-8NKC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Hardener for coating materials or adhesives for industrial or professional use

Not recommended use: Uses other than recommended

1.3. Details of the supplier of the safety data sheet

Company:

BASF SE
67056 Ludwigshafen
GERMANY

Contact address:

BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
UNITED KINGDOM

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Acute Tox. 4 (oral)	H302 Harmful if swallowed.
Skin Corr./Irrit. 2	H315 Causes skin irritation.
Eye Dam./Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT RE 1	H372 Causes damage to organs through prolonged or repeated exposure.
Aquatic Chronic 2	H411 Toxic to aquatic life with long lasting effects.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Pictogram:



Signal Word:
Danger

Hazard Statement:

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P260	Do not breathe dust or mist.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P272	Contaminated work clothing should not be allowed out of the workplace.
P270	Do not eat, drink or smoke when using this product.
P264	Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P391 Collect spillage.
 P314 Get medical advice/attention if you feel unwell.
 P337 + P313 If eye irritation persists: Get medical attention.
 P333 + P313 If skin irritation or rash occurs: Get medical attention.
 P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
 P330 Rinse mouth
 P362 + P364 Take off contaminated clothing and wash it before reuse.
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste collection point.

Hazard determining component(s) for labelling: phthalic anhydride, manganese dioxide, Zinc bis(diethyldithiocarbamate)

2.3. Other hazards

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

inorganic compounds, organic compounds

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

Hazardous ingredients (GHS)

| manganese dioxide

Content (W/W): $\geq 30\%$ - $< 50\%$	Acute Tox. 4 (Inhalation - dust)
CAS Number: 1313-13-9	Acute Tox. 4 (oral)
EC-Number: 215-202-6	STOT RE (Central nervous system) 1
REACH registration number: 01-2119452801-43	H372, H302 + H332

| Zinc bis(diethyldithiocarbamate)

Content (W/W): $\geq 2\%$ - $< 2.5\%$	Acute Tox. 4 (oral)
CAS Number: 14324-55-1	Skin Corr./Irrit. 2
EC-Number: 238-270-9	Skin Sens. 1
	STOT SE (Respiratory system) 3 (irr. to respiratory syst.)
	Aquatic Acute 1
	Aquatic Chronic 1
	Eye Dam./Irrit. 2
	M-factor acute: 10
	M-factor chronic: 10
	H319, H315, H302, H317, H410, H335

| sodium hydroxide

Content (W/W): $\geq 0.5\%$ - $< 1\%$	Met. Corr. 1
CAS Number: 1310-73-2	Skin Corr./Irrit. 1A
EC-Number: 215-185-5	Eye Dam./Irrit. 1
REACH registration number: 01-2119457892-27	H290, H314
INDEX-Number: 011-002-00-6	<u>Specific concentration limit:</u>
	Skin Corr./Irrit. 1A: $\geq 5\%$
	Skin Corr./Irrit. 1B: $2 - < 5\%$
	Skin Corr./Irrit. 2: $0.5 - < 2\%$
	Eye Dam./Irrit. 2: $0.5 - < 2\%$

| phthalic anhydride

Content (W/W): $\geq 0.2\%$ - $< 0.3\%$	Acute Tox. 4 (oral)
CAS Number: 85-44-9	Skin Corr./Irrit. 2
EC-Number: 201-607-5	Eye Dam./Irrit. 1
REACH registration number: 01-2119457017-41	Resp. Sens. 1
INDEX-Number: 607-009-00-4	Skin Sens. 1
	STOT SE 3 (irr. to respiratory syst.)
	H318, H315, H302, H334, H317, H335

| Sodium dimethyldithiocarbamate

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

Content (W/W): $\geq 0.1\%$ - $< 0.2\%$	Aquatic Acute 1
CAS Number: 128-04-1	Aquatic Chronic 1
EC-Number: 204-876-7	M-factor acute: 100
	M-factor chronic: 10
	H400, H410

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

On ingestion:

Summon medical aid without delay. Do not induce vomiting due to aspiration hazard. Rinse mouth immediately with water. Keep at rest.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Eye irritation, allergic symptoms, skin irritation, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Symptomatic treatment (decontamination, vital functions).

Antidote: No known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:
water jet

5.2. Special hazards arising from the substance or mixture

Endangering substances: carbon oxides

Advice: Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

5.3. Advice for fire-fighters

Special protective equipment:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not discharge into the subsoil/soil. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

The relevant fire protection measures should be noted.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: Stove-lacquer EHD0022, Polypropylene (PP), High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethylenetherephthalate (PET), tinned carbon steel (Tinplate), Carbon steel (Iron), Stove-lacquer R 78433, Stainless steel 1.4301 (V2) Further information on storage conditions: Keep container dry. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep away from heat.

Storage stability:

Storage temperature: < 26 °C

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

85-44-9: phthalic anhydride

TWA value 4 mg/m³ (WEL/EH 40 (UK))
STEL value 12 mg/m³ (WEL/EH 40 (UK))
Ceiling limit value/factor: 15 min

1310-73-2: sodium hydroxide

STEL value 2 mg/m³ (WEL/EH 40 (UK))
Ceiling limit value/factor: 15 min

1313-13-9: manganese dioxide

TWA value 0.5 mg/m³ (WEL/EH 40 (UK))
Measured as: manganese (Mn)
TWA value 0.2 mg/m³ (OEL (EU)), Inhalable fraction
Measured as: manganese (Mn)
indicative

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

TWA value 0.05 mg/m³ (OEL (EU)), Respirable fraction
 Measured as: manganese (Mn)
 indicative
 TWA value 0.05 mg/m³ (WEL/EH 40 (UK)), Respirable fraction
 Measured as: manganese (Mn)

Biological limit values (BLV)

No data available.

Components with PNEC

85-44-9: phthalic anhydride

freshwater: 1 mg/l
 marine water: 0.1 mg/l
 intermittent release: 5.6 mg/l
 STP: 10 mg/l
 sediment (freshwater): 3.8 mg/kg
 sediment (marine water): 0.38 mg/kg
 soil: 0.173 mg/kg

128-04-1: Sodium dimethyldithiocarbamate

intermittent release: 0.025 mg/l
 marine water: 0.00078 mg/l
 soil: 0.4053 mg/kg
 sediment (marine water): 0.00162 mg/kg
 sediment (freshwater): 0.0162 mg/kg
 freshwater: 0.0078 mg/l
 oral (secondary poisoning): 1.72 g/kg
 STP: 0.0365 mg/l

1313-13-9: manganese dioxide

freshwater: 0.00014 mg/l
 marine water: 0.000014 mg/l
 sediment (freshwater): 0.037 mg/kg
 sediment (marine water): 0.0037 mg/kg
 soil: 0.028 mg/kg
 STP: 100 mg/l
 intermittent release: 0.00074 mg/l

14324-55-1: Zinc bis(diethyldithiocarbamate)

oral (secondary poisoning): 12 mg/kg
 sediment (freshwater): 0.473 mg/kg
 sediment (marine water): 0.0473 mg/kg
 marine water: 0.032 µg/l
 intermittent release: 2.3 µg/l
 freshwater: 0.32 µg/l
 soil: 0.0944 mg/kg
 STP: 14.3 mg/l

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

Components with DNEL

85-44-9: phthalic anhydride

worker: Long-term exposure- systemic effects, dermal: 10 mg/kg
 worker: Long-term exposure- systemic effects, Inhalation: 32.3 mg/m3
 consumer: Long-term exposure- systemic effects, dermal: 5 mg/kg
 consumer: Long-term exposure- systemic effects, Inhalation: 8.6 mg/m3
 consumer: Long-term exposure- systemic effects, oral: 5 mg/kg

128-04-1: Sodium dimethyldithiocarbamate

worker: Short-term exposure - systemic effects, by inhalation: 3.442 mg/m3
 Repeated dose toxicity
 worker: Long-term exposure- systemic effects, dermal: 123 mg/kg
 Repeated dose toxicity
 worker: Short-term exposure - systemic effects, dermal: 7.533 mg/kg
 Repeated dose toxicity
 worker: Long-term exposure- systemic effects, by inhalation: 1.44 mg/m3
 Repeated dose toxicity

1310-73-2: sodium hydroxide

worker: Long-term exposure - local effects, Inhalation: 1.0 mg/m3

1313-13-9: manganese dioxide

worker: Long-term exposure- systemic effects, Inhalation: 0.2 mg/m3

14324-55-1: Zinc bis(diethyldithiocarbamate)

worker: Long-term exposure- systemic effects, Inhalation: 4 mg/m3

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Personal protective equipment

Respiratory protection:

Respiratory protection required if exposure limit (if available) may be exceeded (Combination filter EN 14387 AB)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

nitrile rubber (NBR) - 0.4 mm coating thickness

butyl rubber gloves - material thickness: 0.5 mm

Performance level 6, corresponding to a breakthrough time of >480 min according to EN ISO 374-1

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Chemical resistant protective clothing according to DIN EN 13034 (Type 6)

General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible.

Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

Environmental exposure controls

For information regarding environmental exposure controls, see Section 6.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form:	liquid
Colour:	brown
Odour:	specific
Odour threshold:	not determined
pH value:	substance/mixture is non-soluble (in water)
Melting point:	not determined
onset of boiling:	not determined
Flash point:	not applicable
Flammability:	not applicable
Lower explosion limit:	not determined
Upper explosion limit:	not determined
Ignition temperature:	not determined
Vapour pressure:	(20 °C) not determined
	(50 °C) not determined

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

Density: 1.650 g/cm³ (DIN 51757)
(20 °C)
Partitioning coefficient n-octanol/water (log K_{ow}):
not applicable
Viscosity, kinematic:
(40 °C)
not determined
Explosion hazard: not explosive
Fire promoting properties: not fire-propagating

9.2. Other information

Self heating ability: It is not a substance capable of spontaneous heating.

Miscibility with water:
immiscible

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

10.4. Conditions to avoid

Avoid direct sunlight. Avoid heat.

10.5. Incompatible materials

Substances to avoid:

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

10.6. Hazardous decomposition products

Possible decomposition products:

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on toxicological effects

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

Acute toxicity

Assessment of acute toxicity:

Of moderate toxicity after single ingestion.

| *Information on: phthalic anhydride*

Experimental/calculated data:

| *LD50 rat (oral): 1,530 mg/kg*

Irritation

Assessment of irritating effects:

Eye contact causes irritation. Skin contact causes irritation.

Respiratory/Skin sensitization

Assessment of sensitization:

Sensitization after skin contact possible.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Based on available data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

Assessment of repeated dose toxicity:
Repeated exposure to small quantities may affect certain organs.

Aspiration hazard

No aspiration hazard expected.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:
There are no test results available for this product. Do not allow to enter drains or waterways. The mixture has been assessed following regulation (EC) No 1272/2008 and is classified for ecotoxicological properties accordingly. See sections 2 and 3 for details.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H₂O):
No data available concerning biodegradation and elimination.

12.3. Bioaccumulative potential

Bioaccumulation potential:
No data available.

12.4. Mobility in soil

Assessment transport between environmental compartments:
Adsorption in soil: No data available.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

12.6. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

Do not discharge into drains/surface waters/groundwater.
Observe national and local legal requirements.

Dispose of the substance/product as special waste in accordance with Directive 2008/98/EC.

Waste key:

Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging:

Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14: Transport Information

Land transport

ADR

UN number or ID number:	UN3082
UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains zinc bis(diethyldithiocarbamate))
Transport hazard class(es):	9, EHSM
Packing group:	III
Environmental hazards:	yes
Special precautions for user:	

RID

UN number or ID number:	UN3082
UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains zinc bis(diethyldithiocarbamate))
Transport hazard class(es):	9, EHSM
Packing group:	III
Environmental hazards:	yes
Special precautions for user:	None known

Inland waterway transport

ADN

UN number or ID number:	UN3082
UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains zinc bis(diethyldithiocarbamate))

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

Transport hazard class(es): 9, EHSM
 Packing group: III
 Environmental hazards: yes
 Special precautions for user: None known

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

UN number or ID number: UN 3082
 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains zinc bis(diethyldithiocarbamate))
 Transport hazard class(es): 9, EHSM
 Packing group: III
 Environmental hazards: yes
 Marine pollutant: YES
 Special precautions for user:

Air transport

IATA/ICAO

UN number or ID number: UN 3082
 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains zinc bis(diethyldithiocarbamate))
 Transport hazard class(es): 9, EHSM
 Packing group: III
 Environmental hazards: yes
 Special precautions for user: None known

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2010/75/EU of the European Parliament and of the Council of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

VOC content: 0.3 %

Paints and varnishes - Determination of volatile organic compound (VOC) content - Part 1: Difference method - Method 1

VOC content: 4.0 g/l

Paints and varnishes - Determination of volatile organic compound (VOC) content - Part 1: Difference method - Method 1

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 46, 3, 75

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):
Listed in above regulation: Hazardous to the Aquatic Environment in Category Chronic 2

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

Chemical Safety Assessment not required

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

SECTION 16: Other Information

Literature and Data Sources: REACH-Regulation (EC) No. 1907/2006. CLP-Regulation (EC) No. 1272/2008.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Acute Tox.	Acute toxicity
Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
Skin Sens.	Skin sensitization
STOT RE	Specific target organ toxicity — repeated exposure
Aquatic Chronic	Hazardous to the aquatic environment - chronic
STOT SE	Specific target organ toxicity — single exposure
Aquatic Acute	Hazardous to the aquatic environment - acute
Met. Corr.	Corrosive to metals
Resp. Sens.	Respiratory sensitization
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H372	Causes damage to organs (Central nervous system) through prolonged or repeated exposure.
H302 + H332	Harmful if swallowed or if inhaled
H410	Very toxic to aquatic life with long lasting effects.
H335	May cause respiratory irritation.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H400	Very toxic to aquatic life.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 06.09.2022

Version: 2.0

Date previous version: 10.09.2019

Previous version: 1.0

Date / First version: 10.09.2019

Product: **Naftoseal MC-650 B-1 Härter**

(ID no. 30739469/SDS_GEN_GB/EN)

Date of print 11.05.2023

Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.