

## CORROSION PREVENTIVE OIL

## NATO CODE C-615

### DESCRIPTION

Nycoprotec 06 is a mineral oil with a technical additive concentrate containing corrosion inhibitors and formulated to neutralize the corrosion effect of the products of combustion of leaded gasoline.



### APPLICATIONS

- Temporary preservation of reciprocating piston aircraft engines
- Long term preservation of piston engines stored in watertight container
- Preservation of helicopter gearboxes during storage

### SPECIFICATIONS \* / OEM's & Airframers reference

- Meets AIR 1503/B Type A
- Meets DEF STAN 91-40 Issue 3 / PX-27

\* **Meets:** The product complies with all the requirements of the specification and has not been formally approved or approval is in progress or the specification is obsolete.

CHARACTERISTIC	UNIT	TYPICAL RESULT	DEF STAN 91-40 ISS.3 LIMIT	TEST METHOD
Appearance	-	Conform	Clear liquid	visual examination
Density at 20°C	kg/dm <sup>3</sup>	0.892	-	ASTM D4052 / IP 226
Kinematic Viscosity at at 100°C at 40°C	mm <sup>2</sup> /s	19.5 228	17.5 – 21.9 Report	ASTM D445 / IP 71
Viscosity Index	-	97	min. 90	ASTM D2270 / IP 226
Flash Point, COC	°C	275	min. 170	ASTM D92 / IP 34
Pour Point	°C	-18	max. -6	ASTM D97 / IP 15
Sulfated Ash	%w	0.12	max. 2.5	ASTM D874 / IP 163

The values above are typical values. They do not constitute any contractual commitment.

Sales specifications are available on request. The present technical data sheet replaces all the previous editions.