

ROYCO[®] 481

CORROSION PREVENTATIVE COMPOUND FOR
AIRCRAFT TURBINE ENGINES

Description

ROYCO 481 is a mineral oil based lubricant formulated with modern additives to provide oxidation and corrosion protection as well as high viscosity index for both low and high temperature fluidity. **ROYCO 481** is approved as a P-10 preservative under MIL-STD-2073-1C for use in gas turbine engines and fuel systems.

Applications

ROYCO 481 is recommended for lubrication of gas turbine engine components and as a flushing and preservative fluid for aircraft fuel systems and components. The high viscosity index provides for operation in a wide range of operating temperatures in high-speed turbines as well as gas turbine engines. **ROYCO 481** may also be considered as the primary turbine engine lubricant in many aircraft turbine engines designed to run on mineral based lubricants.

Features and Benefits

- Offers outstanding rust and corrosion prevention
- Preserves turbojet engines and engine parts
- Ashless additive technology

Specifications

ROYCO 481 meets all requirements of and is qualified to MIL-SPEC: MIL-PRF-6081D Amendment 1, Grade 1010 and 1010N.

ROYCO 481 is approved as a P-10 preservative under MILSPEC: MIL-STD-2073-1C for use in gas turbine engines and fuel systems.

PROPERTIES	TEST METHOD	ROYCO® 481
Kinematic Viscosity, cSt		
@ 37.8°C (100°F)	ASTM D445	10.15
@ -40°C (-40°F)	ASTM D2532	2,446
Viscosity Stability, 3 hrs, @ -40°C, % change	ASTM D2532	0.52
Flash Point, °C (°F)	ASTM D92	300
Pour Point, °C (°F)	ASTM D97.	-62 (-79)
Acid Number (T.A.N.), mq KOH/g	ASTM D974	0.03
Trace Sediment, mL / 200 mL oil	ASTM D2273	0.000
Ash content, 1.2 UM filter, mg/L	FTM 3010	0.51
Gravity, °API	ASTM D4052	29.1
Pounds per Gallon	Calculated	7.34
Copper Corrosion, 100°C, 3 hours, color	ASTM D130	1B
Color, ASTM	ASTM D1500	<0.5

Packaging

ROYCO 481 is available in 5-gallon pails and 55-gallon drums. Other package sizes may be available on special request.

The information contained herein relates to a specific Chemtura product and its use, and is based on information available as of the date hereof. Additional information relating to the product can be obtained from the pertinent Material Safety Data Sheets. Nothing in this Technical Data Sheet constitutes a term or condition of sale nor shall it take precedence over, supersede or modify or be construed to take precedence over, supersede or modify, any of Chemtura's standard or other terms and conditions of sale under which the product is sold by Chemtura. NOTHING IN THIS TECHNICAL DATA SHEET CONSTITUTES, NOR SHALL IT BE CONSTRUED TO CONSTITUTE, A REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE PRODUCT'S CHARACTERISTICS, USE, QUALITY, SAFETY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall constitute permission or recommendation to practice any intellectual property without the permission of the owner. This product is sold only under terms and conditions agreed in writing by Chemtura and the respective buyer and the terms and conditions of such agreements shall in all cases prevail. ANDEROL, ROYCO, AOSyn and PQ and their corresponding logos are trademarks of Chemtura Corporation or one of its subsidiaries. Copyright (c) 2010 Chemtura Corporation. All rights reserved.



Anderol Specialty Lubricants
a division of Chemtura Corporation
215 Merry Lane
East Hanover, New Jersey 07936
Technical Service +1.973.887.7410
Customer Service +1.203.573.4595
Fax +1.203.573.2324
info-anderol@chemtura.com
www.anderol.com